MOSFET – Power, Single, N-Channel, μ8FL

30 V, 44 A

NTTFS4C10N

$V_{(BR)DSS}$	$R_{DS(on)}$ MAX	I_D MAX
30 V	7.4 mΩ @ 10 V	44 A
	11 mΩ @ 4.5 V	



WDFN8
(μ8FL)
CASE 511AB


Features

- Low $R_{DS(on)}$ to Minimize Conduction Losses
- Low Capacitance to Minimize Driver Losses
- Optimized Gate Charge to Minimize Switching Losses
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant


Applications

- DC-DC Converters
- Power Load Switch
- Notebook Battery Management

N-Channel MOSFET



MARKING DIAGRAM



4C10	= Specific Device Code
A	= Assembly Location
Y	= Year
WW	= Work Week
▪	= Pb-Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
NTTFS4C10NTAG	WDFN8 (Pb−Free)	1,500 / Tape & Reel

DISCONTINUED (Note 1)

NTTFS4C10NTWG	WDFN8 (Pb−Free)	5,000 / Tape & Reel

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

1. **DISCONTINUED:** This device is not available. Please contact your **onsemi** representative for information. The most current information on this device may be available on www.onsemi.com.

© Semiconductor Components Industries, LLC, 2013

MAXIMUM RATINGS (T_J = 25 °C unless otherwise stated)

Symbol	Parameter			Value	Unit
V_{DSS}	Drain-to-Source Voltage			30	V
V_{GS}	Gate-to-Source Voltage			±20	V
I_D	Continuous Drain Current $R_{\theta JA}$ (Note 1)	Steady State	T_A = 25 °C	13.3	A
			T_A = 80 °C	9.9	
P_D	Power Dissipation $R_{\theta JA}$ (Note 1)		T_A = 25 °C	2.09	W
I_D	Continuous Drain Current $R_{\theta JA}$ ≤ 10 s (Note 1)		T_A = 25 °C	18.2	A
			T_A = 80 °C	13.6	
P_D	Power Dissipation $R_{\theta JA}$ ≤ 10 s (Note 1)		T_A = 25 °C	3.9	W
I_D	Continuous Drain Current $R_{\theta JA}$ (Note 2)		T_A = 25 °C	8.2	A
			T_A = 80 °C	6.1	
P_D	Power Dissipation $R_{\theta JA}$ (Note 2)		T_A = 25 °C	0.79	W
I_D	Continuous Drain Current $R_{\theta JC}$ (Note 1)		T_C = 25 °C	44	A
			T_C = 80 °C	33	
P_D	Power Dissipation $R_{\theta JC}$ (Note 1)		T_C = 25 °C	23.6	W
I_{DM}	Pulsed Drain Current	T_A = 25 °C, t_p = 10 μs		128	A
T_J, T_{stg}	Operating Junction and Storage Temperature			−55 to +150	°C
I_S	Source Current (Body Diode)			20	A
dV/dt	Drain to Source dV/dt			6.0	V/ns
E_{AS}	Single Pulse Drain-to-Source Avalanche Energy (T_J = 25 °C, V_{DD} = 50 V, V_{GS} = 10 V, I_L = 25 A_{pk}, L = 0.1 mH, R_G = 25 Ω) (Note 3)			31	mJ
T_L	Lead Temperature for Soldering Purposes (1/8″ from case for 10 s)			260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Surface-mounted on FR4 board using 1 sq-in pad, 1 oz Cu.
2. Surface-mounted on FR4 board using the minimum recommended pad size.
3. This is the absolute maximum ratings. Parts are 100% tested at T_J = 25 °C, V_{GS} = 10 V, I_L = 17 A, E_{AS} = 14 mJ.

THERMAL RESISTANCE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Junction-to-Case (Drain)	5.3	°C/W
$R_{\theta JA}$	Junction-to-Ambient – Steady State (Note 4)	59.9	
$R_{\theta JA}$	Junction-to-Ambient – Steady State (Note 5)	157.8	
$R_{\theta JA}$	Junction-to-Ambient – (t ≤ 10 s) (Note 4)	31.8	

4. Surface-mounted on FR4 board using 1 sq-in pad, 1 oz Cu.
5. Surface-mounted on FR4 board using the minimum recommended pad size.

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (T_J = 25 °C unless otherwise specified)

Symbol	Parameter	Test Condition		Min	Typ	Max	Unit
OFF CHARACTERISTICS							
$V_{(BR)DSS}$	Drain-to-Source Breakdown Voltage	V_{GS} = 0 V, I_D = 250 μA		30	–	–	V
$V_{(BR)DSS}$ t	Drain-to-Source Breakdown Voltage (transient)	V_{GS} = 0 V, $I_{D(aval)}$ = 7.1 A, T_{case} = 25 °C, $t_{transient}$ = 100 ns		34	–	–	V
$V_{(BR)DSS}$ / T_J	Drain-to-Source Breakdown Voltage Temperature Coefficient			–	14.5	–	mV/° C
I_{DSS}	Zero Gate Voltage Drain Current	V_{GS} = 0 V, V_{DS} = 24 V	T_J = 25 °C	–	–	1.0	μA
			T_J = 125 °C	–	–	10	
I_{GSS}	Gate-to-Source Leakage Current	V_{DS} = 0 V, V_{GS} = ±20 V		–	–	±100	nA
ON CHARACTERISTICS (Note 6)							
$V_{GS(TH)}$	Gate Threshold Voltage	V_{GS} = V_{DS}, I_D = 250 μA		1.3	–	2.2	V
$V_{GS(TH)}$/ T_J	Negative Threshold Temperature Coefficient			–	4.5	–	mV/°C
$R_{DS(on)}$	Drain-to-Source On Resistance	V_{GS} = 10 V	I_D = 30 A	–	5.9	7.4	mΩ
		V_{GS} = 4.5 V	I_D = 15 A	–	8.8	11	
g_{FS}	Forward Transconductance	V_{DS} = 1.5 V, I_D = 15 A		–	43	–	S
R_G	Gate Resistance	T_A = 25 °C		–	1.0	–	Ω
CHARGES AND CAPACITANCES							
C_{ISS}	Input Capacitance	V_{GS} = 0 V, f = 1 MHz, V_{DS} = 15 V		–	993	–	pF
C_{OSS}	Output Capacitance			–	574	–	
C_{RSS}	Reverse Transfer Capacitance			–	163	–	
C_{RSS}/C_{I} SS	Capacitance Ratio	V_{GS} = 0 V, V_{DS} = 15 V, f = 1 MHz		–	0.16 4	–	
$Q_{G(TOT)}$	Total Gate Charge	V_{GS} = 4.5 V, V_{DS} = 15 V; I_D = 30 A		–	9.7	–	nC
$Q_{G(TH)}$	Threshold Gate Charge			–	1.5	–	
Q_{GS}	Gate-to-Source Charge			–	2.8	–	
Q_{GD}	Gate-to-Drain Charge			–	4.8	–	
V_{GP}	Gate Plateau Voltage			–	3.2	–	V
$Q_{G(TOT)}$	Total Gate Charge	V_{GS} = 10 V, V_{DS} = 15 V; I_D = 30 A			18.6	–	nC
SWITCHING CHARACTERISTICS (Note 7)							
$t_{d(ON)}$	Turn-On Delay Time	V_{GS} = 4.5 V, V_{DS} = 15 V, I_D = 15 A, R_G = 3.0 Ω		–	9.0	–	ns
t_r	Rise Time			–	30	–	
$t_{d(OFF)}$	Turn-Off Delay Time			–	14	–	
t_f	Fall Time			–	7.0	–	
$t_{d(ON)}$	Turn-On Delay Time	V_{GS} = 10 V, V_{DS} = 15 V, I_D = 15 A, R_G = 3.0 Ω		–	6.0	–	ns
t_r	Rise Time			–	25	–	
$t_{d(OFF)}$	Turn-Off Delay Time			–	18	–	
t_f	Fall Time			–	4.0	–	

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (T_J = 25 °C unless otherwise specified) (continued)

Symbol	Parameter	Test Condition		Min	Typ	Max	Unit
DRAIN-SOURCE DIODE CHARACTERISTICS							
V_{SD}	Forward Diode Voltage	V_{GS} = 0 V, I_S = 10 A	T_J = 25 °C	–	0.80	1.1	V
			T_J = 125 °C	–	0.67	–	
t_{RR}	Reverse Recovery Time	V_{GS} = 0 V, dIS/dt = 100 A/μs, I_S = 30 A		–	23.3	–	ns
t_a	Charge Time			–	12.7	–	
t_b	Discharge Time			–	10.6	–	
Q_{RR}	Reverse Recovery Charge			–	8.3	–	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

6. Pulse Test: pulse width ≤ 300 μs, duty cycle ≤ 2%.
7. Switching characteristics are independent of operating junction temperatures.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. V_{GS}




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS (continued)




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area




Figure 12. Maximum Avalanche Energy vs. Starting Junction Temperature

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS (continued)




Figure 13. Thermal Response




Figure 14. G_{FS} vs. I_D




Figure 15. Avalanche Characteristics

Share Feedback
Your Opinion Matters

REVISION HISTORY

Revision	Description of Changes	Date
4	NTTFS4C10NTWG OPN Marked as Discontinued + Rebranded the Data Sheet to **onsemi** format.	2/13/2026

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.


Share Feedback
Your Opinion Matters



SCALE 2:1


WDFN8 3.3x3.3, 0.65P
CASE 511AB
ISSUE D

DATE 23 APR 2012



NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION D1 AND E1 DO NOT INCLUDE MOLD FLASH PROTRUSIONS OR GATE BURRS.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	0.70	0.75	0.80	0.028	0.030	0.031
A1	0.00	---	0.05	0.000	---	0.002
b	0.23	0.30	0.40	0.009	0.012	0.016
c	0.15	0.20	0.25	0.006	0.008	0.010
D	3.30 BSC			0.130 BSC		
D1	2.95	3.05	3.15	0.116	0.120	0.124
D2	1.98	2.11	2.24	0.078	0.083	0.088
E	3.30 BSC			0.130 BSC		
E1	2.95	3.05	3.15	0.116	0.120	0.124
E2	1.47	1.60	1.73	0.058	0.063	0.068
E3	0.23	0.30	0.40	0.009	0.012	0.016
e	0.65 BSC			0.026 BSC		
G	0.30	0.41	0.51	0.012	0.016	0.020
K	0.65	0.80	0.95	0.026	0.032	0.037
L	0.30	0.43	0.56	0.012	0.017	0.022
L1	0.06	0.13	0.20	0.002	0.005	0.008
M	1.40	1.50	1.60	0.055	0.059	0.063
θ	0 °	---	12 °	0 °	---	12 °




GENERIC MARKING DIAGRAM*



XXXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

SOLDERING FOOTPRINT*



DIMENSION: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	**98AON30561E**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**WDFN8 3.3X3.3, 0.65P**	**PAGE 1 OF 1**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.