
MOSFET - Power, Single N-Channel, Source Down 33, WDFN9
25 V, 0.58 mΩ, 310 A

NTTFSSH0D7N02X


$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX	I_D MAX
25 V	0.58 mΩ @ V_{GS} = 10 V	310 A
	0.80 mΩ @ V_{GS} = 4.5 V	

Features
- Advanced Source−Down Package Technology (3.3 x 3.3 mm) with Excellent Thermal Conduction
- Ultra Low $R_{DS(on)}$ to Improve System Efficiency
- Low Q_G and Capacitance to Minimize Driving and Switching Losses
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

Applications
- High Switching Frequency DC−DC Conversion
- Synchronous Rectifier



N−CHANNEL MOSFET



WDFN9
CASE 511EB

MARKING DIAGRAM



0D7N02 = Specific Device Code
A = Assembly Location
WL = Wafer Lot
Y = Year
WW = Work Week

ORDERING INFORMATION
See detailed ordering and shipping information on page 6 of this data sheet.

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Parameter		Symbol	Value	Unit
Drain−to−Source Voltage		V_{DSS}	25	V
Gate−to−Source Voltage		V_{GS}	−12/+16	V
Continuous Drain Current (Notes 1, 2)	T_C = 25°C	I_D	310	A
	T_C = 100°C		196	
Power Dissipation (Note 1)	T_C = 25°C	P_D	87	W
Pulsed Drain Current	T_C = 25°C, t_p = 100 μs	I_{DM}	1342	A
Operating Junction and Storage Temperature Range		T_J, T_{stg}	−55 to +150	°C
Source Current (Body Diode)		I_S	146	A
Single Pulse Avalanche Energy (Note 3) (I_{PK} = 62 A)		E_{AS}	192	mJ
Lead Temperature for Soldering Purposes (1/8″ from case for 10 s)		T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. The entire application environment impacts the thermal resistance values shown, they are not constants and are valid for the particular conditions noted.
2. Surface−mounted on FR4 board using a 1 in^2 pad size, 1 oz Cu pad.
3. E_{AS} of 192 mJ is based on started T_J = 25°C, I_{AS} = 62 A, V_{GS} = 10 V, 100% avalanche tested.

© Semiconductor Components Industries, LLC, 2023

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	1.4	°C/W
Thermal Resistance, Junction−to−Ambient (Note 4)	$R_{\theta JA}$	60	

4. Surface−mounted on FR4 board using a 1 in^2 pad size, 1 oz Cu pad.

ELECTRICAL CHARACTERISTICS (T_J = 25 °C unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 1 mA	25			V
Drain−to−Source Breakdown Voltage Temperature Coefficient	$\Delta V_{(BR)DSS}/\Delta T_J$	I_D = 1 mA, Referenced to 25 °C		21		mV/°C
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 20 V			10	μA
		V_{DS} = 20 V, TJ = 125 °C			100	
Gate−to−Source Leakage Current	I_{GSS}	V_{DS} = 0 V, V_{GS} = +16 V			100	nA
ON CHARACTERISTICS						
Drain−to−Source On Resistance	$R_{DS(ON)}$	V_{GS} = 10 V, I_D = 24 A		0.51	0.58	mΩ
		V_{GS} = 6 V, I_D = 19 A		0.56	0.65	
		V_{GS} = 4.5 V, I_D = 19 A		0.66	0.80	
Gate Threshold Voltage	$V_{GS(TH)}$	V_{GS} = V_{DS}, I_D = 484 μA	1.1		2.0	V
Gate Threshold Voltage Temperature Coefficient	$\Delta V_{GS(TH)}/\Delta T_J$	V_{GS} = V_{DS}, I_D = 484 μA		−3		mV/°C
Forward Transconductance	g_{FS}	V_{DS} = 5 V, I_D = 24 A		190		S
CHARGES, CAPACITANCES & GATE RESISTANCE						
Input Capacitance	C_{ISS}	V_{GS} = 0 V, V_{DS} = 12 V, f = 1 MHz		3980		pF
Output Capacitance	C_{OSS}			1160		
Reverse Transfer Capacitance	C_{RSS}			124		
Output Charge	Q_{OSS}			22		nC
Total Gate Charge	$Q_{G(TOT)}$	V_{GS} = 4.5 V, V_{DD} = 12 V; I_D = 24 A		25		
		V_{GS} = 6 V, V_{DD} = 12 V; I_D = 24 A		33		
		V_{GS} = 10 V, V_{DD} = 12 V; I_D = 24 A		55		
Threshold Gate Charge	$Q_{G(TH)}$			5.7		
Gate−to−Source Charge	Q_{GS}			9.7		
Gate−to−Drain Charge	Q_{GD}			4.1		
Gate Plateau Voltage	V_{GP}			2.5		V
Gate Resistance	R_G	f = 1 MHz		0.4		Ω
SWITCHING CHARACTERISTICS						
Turn−On Delay Time	$t_{d(ON)}$	Resistive Load, V_{GS} = 0/10 V, V_{DD} = 12 V, I_D = 24 A, R_G = 2.5 Ω		4		ns
Rise Time	t_r			6		
Turn−Off Delay Time	$t_{d(OFF)}$			26		
Fall Time	t_f			57		
SOURCE−TO−DRAIN DIODE CHARACTERISTICS						
Forward Diode Voltage	V_{SD}	V_{GS} = 0 V, I_S = 24 A, T_J = 25 °C		0.76	1.2	V
		V_{GS} = 0 V, I_S = 24 A, T_J = 125 °C		0.63		

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (T_J = 25 °C unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
SOURCE−TO−DRAIN DIODE CHARACTERISTICS						
Reverse Recovery Time	t_{RR}	V_{GS} = 0 V, I_S = 24 A, dI/dt = 700 A/μs, V_{DD} = 12 V		17		ns
Charge Time	t_a			10		
Discharge Time	t_b			7		
Reverse Recovery Charge	Q_{RR}			58		nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Resistance vs. Gate Voltage




Figure 4. On−Resistance vs. Drain Current




Figure 5. Normalized ON Resistance vs. Junction Temperature




Figure 6. Drain Leakage Current vs Drain Voltage

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Characteristics




Figure 11. Safe Operating Area (SOA)




Figure 12. Avalanche Current vs Pulse Time (UIS)

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 13. IDM vs Pulse Width





Figure 14. Transient Thermal Response

ORDERING INFORMATION

Device	Marking	Package	Shipping†
NTTFSSH0D7N02X	0D7N02	WDFN9 (Pb−Free)	3000 / Tape & Reel


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Share Feedback
Your Opinion Matters




WDFN9 3.3x3.3, 0.65P
CASE 511EB
ISSUE B


DATE 21 JUL 2021



TOP VIEW




FRONT VIEW




DETAIL A
SCALE: 2:1

NOTES:
1. CONTROLLING DIMENSION: MILLIMETERS
2. COPLANARITY APPLIES TO THE EXPOSED PADS AS WELL AS THE TERMINALS.
3. DIMENSIONS D1, D2, E1 AND E2 DO NOT INCLUDE MOLD FLASH.
4. SEATING PLANE IS DEFINED BY THE TERMINALS. "A1" IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT OF THE PACKAGE BODY.

UNIT IN MILLIMETER			
DIM	MIN	NOM	MAX
A	0.70	0.75	0.80
A1	0.00	0.02	0.05
A3		0.20 REF	
b	0.25	0.30	0.35
b2	0.37	0.42	0.47
D	3.20	3.30	3.40
D1	2.31	2.41	2.51
D2	1.58	1.68	1.78
D3	2.31	2.41	2.51
E	3.20	3.30	3.40
E1	1.50	1.60	1.70
E2	0.84	0.94	1.04
E3	0.20	0.25	0.30
E4	0.35	0.45	0.55
e		0.650 BSC	
e/2		0.325 BSC	
k		0.75 REF	
k1		0.45 REF	
L	0.73	0.83	0.93
L1	0.10	0.20	0.30
L4	0.40	0.50	0.60



BOTTOM VIEW



LAND PATTERN
RECOMMENDATION

*FOR ADDITIONAL INFORMATION ON OUR PB−FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
WL = Wafer Lot
Y = Year
WW = Work Week

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON08290H**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**WDFN9 3.3x3.3, 0.65P**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2018

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.