ON Semiconductor

Is Now



To learn more about onsemi™, please visit our website at
www.onsemi.com

onsemi and onsemi and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner. Other names and brands may be claimed as the property of others.

NVATS5A107PLZ

Power MOSFET
–40 V, 17 mΩ, –55 A, P-Channel

ON Semiconductor®

www.onsemi.com


Automotive Power MOSFET designed for compact and efficient designs and including high thermal performance.
AEC-Q101 qualified MOSFET and PPAP capable suitable for automotive applications.


V_{DSS}	R_{DS}(on) Max	I_D Max
–40 V	17 mΩ @ –10 V	–55 A
	26 mΩ @ –4.5 V	

Features
- Low On-Resistance
- High Current Capability
- 100% Avalanche Tested
- AEC-Q101 qualified and PPAP capable
- ATPAK package is pin-compatible with DPAK (TO-252)
- Pb-Free, Halogen Free and RoHS compliance

Typical Applications
- Reverse Battery Protection
- Load Switch
- Automotive Front Lighting
- Automotive Body Controllers


ELECTRICAL CONNECTION
P-Channel





ATPAK

MARKING



SPECIFICATIONS
ABSOLUTE MAXIMUM RATING at Ta = 25°C (Note 1)

Parameter	Symbol	Value	Unit
Drain to Source Voltage	V_{DSS}	–40	V
Gate to Source Voltage	V_{GSS}	±20	V
Drain Current (DC)	I_D	–55	A
Drain Current (Pulse) PW ≤ 10 μs, duty cycle ≤ 1%	I_{DP}	–165	A
Power Dissipation Tc = 25°C	P_D	60	W
Operating Junction and Storage Temperature	Tj, Tstg	–55 to +175	°C
Avalanche Energy (Single Pulse) (Note 2)	E_{AS}	80	mJ
Avalanche Current (Note 3)	I_{AV}	–25	A

Note 1 : Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.
2 : V_{DD} = –10 V, L = 200 μH, I_{AV} = –25 A
3 : L ≤ 200 μH, Single pulse

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Value	Unit
Junction to Case Steady State (Tc = 25°C)	$R_{\theta JC}$	2.5	°C/W
Junction to Ambient (Note 4)	$R_{\theta JA}$	80.1	°C/W

Note 4 : Surface mounted on FR4 board using a 130 mm^2, 1 oz. Cu pad.

ORDERING INFORMATION
See detailed ordering and shipping information on page 6 of this data sheet.


© Semiconductor Components Industries, LLC, 2016


ELECTRICAL CHARACTERISTICS at Ta = 25°C (Note 5)


Parameter	Symbol	Conditions	Value			Unit
			min	typ	max	
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	I_D = −1 mA, V_{GS} = 0 V	−40			V
Zero-Gate Voltage Drain Current	I_{DSS}	V_{DS} = −40 V, V_{GS} = 0 V			−1	μA
Gate to Source Leakage Current	I_{GSS}	V_{GS} = ±16 V, V_{DS} = 0 V			±10	μA
Gate Threshold Voltage	$V_{GS}(th)$	V_{DS} = −10 V, I_D = −1 mA	−1.2		−2.6	V
Forward Transconductance	g_{FS}	V_{DS} = −10 V, I_D = −25 A		40		S
Static Drain to Source On-State Resistance	$R_{DS}(on)1$	I_D = −25 A, V_{GS} = −10 V		13	17	mΩ
	$R_{DS}(on)2$	I_D = −13 A, V_{GS} = −4.5 V		18.5	26	mΩ
Input Capacitance	Ciss	V_{DS} = −20 V, f = 1 MHz		2,400		pF
Output Capacitance	Coss			330		pF
Reverse Transfer Capacitance	Crss			240		pF
Turn-ON Delay Time	$t_d(on)$	See Fig.1		17		ns
Rise Time	t_r			260		ns
Turn-OFF Delay Time	$t_d(off)$			190		ns
Fall Time	t_f			160		ns
Total Gate Charge	Qg	V_{DS} = −20 V, V_{GS} = −10 V, I_D = −50 A		47		nC
Gate to Source Charge	Qgs			11.5		nC
Gate to Drain “Miller” Charge	Qgd			8		nC
Forward Diode Voltage	V_{SD}	I_S = −50 A, V_{GS} = 0 V		−1.02	−1.5	V


Note 5 : Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


Fig.1 Switching Time Test Circuit






ID – VDS
Tc=25°C
Single pulse
–10.0V
–8.0V
–6.0V
–4.5V
–4.0V
–16.0V
VGS= –3.5V
Drain Current, ID – A
Drain-to-Source Voltage, VDS – V
IT15168



ID – VGS
VDS= –10V
Single pulse
Tc= –25°C
75°C
25°C
Drain Current, ID – A
Gate-to-Source Voltage, VGS – V
IT15169



RDS(on) – VGS
Tc=25°C
Single pulse
ID= –13A
–25A
Static Drain-to-Source
On-State Resistance, RDS(on) – mΩ
Gate-to-Source Voltage, VGS – V
IT15170



RDS(on) – Tc
Single pulse
VGS= –4.5V, ID= –13A
VGS= –10V, ID= –25A
Static Drain-to-Source
On-State Resistance, RDS(on) – mΩ
Case Temperature, Tc – °C
HD160823



gFS – ID
VDS= –10V
Single pulse
25°C
Tc= –25°C
75°C
Forward Transconductance, gFS – S
Drain Current, ID – A
HD15172



IS – VSD
VGS=0V
Single pulse
Tc=75°C
25°C
–25°C
Source Current, IS – A
Forward Diode Voltage, VSD – V
HD15173



SW Time – ID
VDD= –20V
VGS= –10V
td(off)
tf
tr
td(on)
Switching Time, SW Time – ns
Drain Current, ID – A
IT15174



Ciss, Coss, Crss – VDS
f=1MHz
Ciss
Coss
Crss
Ciss, Coss, Crss – pF
Drain-to-Source Voltage, VDS – V
IT15175


VGS – Qg
VDS= –20V
ID= –50A
Gate-to-Source Voltage, VGS – V
Total Gate Charge, Qg – nC
IT15176


S O A
IDP= –165A(PW≤10μs)
ID= –55A
10μs
100μs
1ms
10ms
100ms
DC operation
Operation in this area is limited by RDS(on).
Tc=25°C
Single pulse
Drain Current, ID – A
Drain-to-Source Voltage, VDS – V
HD160530



PD – Tc
Power Dissipation, PD – W
Case Temperature, Tc – °C
HD160530



EAS – Ta
Avalanche Energy derating factor – %
Ambient Temperature, Ta – °C
HD160530


RθJC – Pulse Time
RθJC=2.5°C/W
Duty Cycle=0.5
0.2
0.1
0.05
0.02
0.01
Single Pulse
Thermal Resistance, RθJC – °C/W
Pulse Time, PT – s
HD160530

PACKAGE DIMENSIONS
unit : mm

DPAK (Single Gauge) / ATPAK
CASE 369AM
ISSUE O






Pin2 is idle pin with electrical designation only carried

*1:Lot indication

1 : Gate
2 : Drain
3 : Source
4 : Drain

RECOMMENDED SOLDERING FOOTPRINT



ORDERING INFORMATION

Device	Marking	Package	Shipping (Qty / Packing)
NVATS5A107PLZT4G	ATP107	DPAK(Single Gauge) / ATPAK (Pb-Free / Halogen Free)	3,000 / Tape & Reel

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D. http://www.onsemi.com/pub_link/Collateral/BRD8011-D.PDF

Note on usage : Since the NVATS5A107PLZ is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.