
MOSFET - SiC Power, Single N-Channel, TO247-4L


650 V, 44 mΩ, 47 A

NVH4L060N065SC1

$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX	I_D MAX
650 V	70 mΩ @ 18 V	47 A



N−CHANNEL MOSFET



TO247−4L
CASE 340CJ

Features

- Typ. $R_{DS(on)}$ = 44 mΩ @ V_{GS} = 18 V
  Typ. $R_{DS(on)}$ = 60 mΩ @ V_{GS} = 15 V
- Ultra Low Gate Charge ($Q_{G(tot)}$ = 74 nC)
- Low Capacitance (C_{oss} = 133 pF)
- 100% Avalanche Tested
- AEC−Q101 Qualified and PPAP Capable
- This Device is Pb−Free and is RoHS Compliant

Typical Applications

- Automotive On Board Charger
- Automotive DC/DC Converter for EV/HEV

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Parameter			Symbol	Value	Unit
Drain−to−Source Voltage			V_{DSS}	650	V
Gate−to−Source Voltage			V_{GS}	−8/+22	V
Recommended Operation Values of Gate−to−Source Voltage		T_C < 175°C	V_{GSop}	−5/+18	V
Continuous Drain Current (Note 1)	Steady State	T_C = 25°C	I_D	47	A
Power Dissipation (Note 1)	Steady State	T_C = 25°C	P_D	176	W
Continuous Drain Current (Note 1)	Steady State	T_C = 100°C	I_D	33	A
Power Dissipation (Note 1)	Steady State	T_C = 100°C	P_D	88	W
Pulsed Drain Current (Note 2)	T_C = 25°C		I_{DM}	152	A
Operating Junction and Storage Temperature Range			T_J, T_{stg}	−55 to +175	°C
Source Current (Body Diode)			I_S	35	A
Single Pulse Drain−to−Source Avalanche Energy ($I_{L(pk)}$ = 10.1 A, L = 1 mH) (Note 3)			E_{AS}	51	mJ
Maximum Lead Temperature for Soldering (1/8″ from case for 5 s)			T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
2. Repetitive rating, limited by max junction temperature.
3. EAS of 51 mJ is based on starting T_J = 25°C; L = 1 mH, I_{AS} = 10.1 A, V_{DD} = 50 V, V_{GS} = 18 V.

MARKING DIAGRAM



H4L060065SC1 = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Lot Traceability

ORDERING INFORMATION

Device	Package	Shipping
NVH4L060N065SC1	TO247−4L	30 Units / Tube

© Semiconductor Components Industries, LLC, 2021

THERMAL RESISTANCE MAXIMUM RATINGS

Parameter	Symbol	Max	Unit
Junction−to−Case − Steady State (Note 1)	$R_{\theta JC}$	0.85	°C/W
Junction−to−Ambient − Steady State (Note 1)	$R_{\theta JA}$	40	

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
OFF CHARACTERISTICS							
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 1 mA		650	–	–	V
Drain−to−Source Breakdown Voltage Temperature Coefficient	$V_{(BR)DSS}/T_J$	I_D = 20 mA, referenced to 25°C		–	0.15	–	V/°C
Zero Gate Voltage Drain Current	I_{DSS}	V_{GS} = 0 V, V_{DS} = 650 V	T_J = 25°C	–	–	10	μA
			T_J = 175°C	–	–	1	mA
Gate−to−Source Leakage Current	I_{GSS}	V_{GS} = +18/−5 V, V_{DS} = 0 V		–	–	250	nA
ON CHARACTERISTICS (Note 2)							
Gate Threshold Voltage	$V_{GS(TH)}$	V_{GS} = V_{DS}, I_D = 6.5 mA		1.8	2.8	4.3	V
Recommended Gate Voltage	V_{GOP}			−5	–	+18	V
Drain−to−Source On Resistance	$R_{DS(on)}$	V_{GS} = 15 V, I_D = 20 A, T_J = 25°C		–	60	–	mΩ
		V_{GS} = 18 V, I_D = 20 A, T_J = 25°C		–	44	70	
		V_{GS} = 18 V, I_D = 20 A, T_J = 175°C		–	50	–	
Forward Transconductance	g_{FS}	V_{DS} = 10 V, I_D = 20 A		–	12	–	S
CHARGES, CAPACITANCES & GATE RESISTANCE							
Input Capacitance	C_{ISS}	V_{GS} = 0 V, f = 1 MHz, V_{DS} = 325 V		–	1473	–	pF
Output Capacitance	C_{OSS}			–	133	–	
Reverse Transfer Capacitance	C_{RSS}			–	13	–	
Total Gate Charge	$Q_{G(TOT)}$	V_{GS} = −5/18 V, V_{DS} = 520 V, I_D = 20 A		–	74	–	nC
Gate−to−Source Charge	Q_{GS}			–	20	–	
Gate−to−Drain Charge	Q_{GD}			–	23	–	
Gate−Resistance	R_G	f = 1 MHz		–	3.9	–	Ω
SWITCHING CHARACTERISTICS							
Turn−On Delay Time	$t_{d(ON)}$	V_{GS} = −5/18 V, V_{DS} = 400 V, I_D = 20 A, R_G = 2.2 Ω inductive load		–	11	–	ns
Rise Time	t_r			–	14	–	
Turn−Off Delay Time	$t_{d(OFF)}$			–	24	–	
Fall Time	t_f			–	11	–	
Turn−On Switching Loss	E_{ON}			–	45	–	μJ
Turn−Off Switching Loss	E_{OFF}			–	18	–	
Total Switching Loss	E_{tot}			–	63	–	
DRAIN−SOURCE DIODE CHARACTERISTICS							
Continuous Drain−Source Diode Forward Current	I_{SD}	V_{GS} = −5 V, T_J = 25°C		–	–	35	A
Pulsed Drain−Source Diode Forward Current (Note 2)	I_{SDM}			–	–	152	
Forward Diode Voltage	V_{SD}	V_{GS} = −5 V, I_{SD} = 20 A, T_J = 25°C		–	4.3	–	V

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified) (continued)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
DRAIN−SOURCE DIODE CHARACTERISTICS						
Reverse Recovery Time	t_{RR}	V_{GS} = −5/18 V, I_{SD} = 20 A, dI_S/dt = 1000 A/μs	–	17.7	–	ns
Reverse Recovery Charge	Q_{RR}		–	90.6	–	nC
Reverse Recovery Energy	E_{REC}		–	8.7	–	μJ
Peak Reverse Recovery Current	I_{RRM}		–	10.2	–	A
Charge time	Ta		–	9.8	–	ns
Discharge time	Tb		–	7.8	–	ns

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL CHARACTERISTICS




Figure 1. On−Region Characteristics




Figure 2. Normalized On−Resistance vs. Drain Current and Gate Voltage




Figure 3. On−Resistance Variation with Temperature




Figure 4. On−Resistance vs. Gate−to−Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Diode Forward Voltage vs. Current

TYPICAL CHARACTERISTICS




Figure 7. Gate−to−Source Voltage vs. Total Charge




Figure 8. Capacitance vs. Drain−to−Source Voltage




Figure 9. Unclamped Inductive Switching Capability




Figure 10. Maximum Continuous Drain Current vs. Case Temperature




Figure 11. Safe Operating Area




Figure 12. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS





Figure 13. Junction−to−Case Thermal Response

PACKAGE DIMENSIONS

TO−247−4LD
CASE 340CJ
ISSUE A



NOTES:

A. NO INDUSTRY STANDARD APPLIES TO THIS PACKAGE.
B. DIMENSIONS ARE EXCLUSIVE OF BURRS,MOLD FLASH,AND TIE BAR EXTRUSIONS.
C. ALL DIMENSIONS ARE IN MILLIMETERS.
D. DRAWING CONFORMS TO ASME Y14.5-2009.

DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.80	5.00	5.20
A1	2.10	2.40	2.70
A2	1.80	2.00	2.20
b	1.07	1.20	1.33
b1	1.20	1.40	1.60
b2	2.02	2.22	2.42
c	0.50	0.60	0.70
D	22.34	22.54	22.74
D1	16.00	16.25	16.50
D2	0.97	1.17	1.37
e	2.54 BSC		
e1	5.08 BSC		
E	15.40	15.60	15.80
E1	12.80	13.00	13.20
E/2	4.80	5.00	5.20
L	18.22	18.42	18.62
L1	2.42	2.62	2.82
p	3.40	3.60	3.80
p1	6.60	6.80	7.00
Q	5.97	6.17	6.37
S	5.97	6.17	6.37

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi's** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT
North American Technical Support:
Voice Mail: 1 800−282−9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:
Phone: 00421 33 790 2910
For additional information, please contact your local Sales Representative

◊

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.