N-Channel Power MOSFET

FEATURES

- Super-Junction technology
- High performance good FOM
- High ruggedness performance
- High commutation performance
- 100% UIS & Rg tested
- RoHS Compliant
- Halogen-free


APPLICATIONS


- Power Supply
- Lighting

KEY PERFORMANCE PARAMETERS		
PARAMETER	**VALUE**	**UNIT**
V_{DS} @ $T_{j,max}$	650	V
$R_{DS(on)}$ (max)	390	mΩ
$Q_{g,typ}$	21	nC

Pb-Free RoHS COMPLIANT HALOGEN FREE

TO-252 (DPAK)





Note: MSL 3 (Moisture Sensitivity Level) per J-STD-020

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)				
PARAMETER		**SYMBOL**	**LIMIT**	**UNIT**
Drain-Source Voltage		V_{DS}	600	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current (Note 1)	T_C = 25°C	I_D	11	A
	T_C = 100°C		7	A
Pulsed Drain Current (Note 2)		I_{DM}	33	A
Total Power Dissipation @ T_C = 25°C		P_D	125	W
Single Pulse Avalanche Energy (Note 3)		E_{AS}	300	mJ
Single Pulse Avalanche Current (Note 3)		I_{AS}	3.5	A
Operating Junction and Storage Temperature Range		T_J, T_{STG}	- 55 to +150	°C

THERMAL PERFORMANCE			
PARAMETER	**SYMBOL**	**LIMIT**	**UNIT**
Junction to Case Thermal Resistance	$R_{\Theta JC}$	1	°C/W
Junction to Ambient Thermal Resistance	$R_{\Theta JA}$	50	°C/W

Note: Device on a PCB FR4 with 1 in^2 (single layer, 2 oz thickness) copper area for drain connection.

ELECTRICAL SPECIFICATIONS (T_A = 25°C unless otherwise noted)						
PARAMETER	**CONDITIONS**	**SYMBOL**	**MIN**	**TYP**	**MAX**	**UNIT**
Static (Note 4)						
Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 1mA	BV_{DSS}	600	--	--	V
Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 1mA	$V_{GS(TH)}$	3	4.5	5	V
Gate Body Leakage	V_{GS} = ± 20V, V_{DS} = 0V	I_{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V_{DS} = 600V, V_{GS} = 0V	I_{DSS}	--	--	100	μA
Drain-Source On-State Resistance	V_{GS} = 10V, I_D = 3.8A	$R_{DS(on)}$	--	350	390	mΩ
Dynamic (Note 5)						
Total Gate Charge	V_{DS} = 300V, I_D = 9A, V_{GS} = 10V	Q_g	--	21	--	nC
Gate-Source Charge		Q_{gs}	--	6	--	
Gate-Drain Charge		Q_{gd}	--	10	--	
Input Capacitance	V_{DS} = 300V, V_{GS} = 0V, f = 1.0MHz	C_{iss}	--	783	--	pF
Output Capacitance		C_{oss}	--	27	--	
Reverse Transfer Capacitance		C_{rss}	--	13	--	
Gate Resistance	f = 1.0MHz	R_g	0.6	2	4	Ω
Switching (Note 6)						
Turn-On Delay Time	V_{DD} = 300V, R_G = 10Ω, I_D = 5.5A, V_{GS} = 10V	$t_{d(on)}$	--	22	--	ns
Turn-On Rise Time		t_r	--	26	--	
Turn-Off Delay Time		$t_{d(off)}$	--	41	--	
Turn-Off Fall Time		t_f	--	19	--	
Source-Drain Diode (Note 4)						
Body-Diode Continuous Forward Current		I_S	--	--	11	A
Body-Diode Pulsed Current		I_{SM}	--	--	33	A
Forward Voltage	I_S = 11A, V_{GS} = 0V	V_{SD}	--	--	1.5	V
Reverse Recovery Time	I_S = 11A dI$_F$/dt = 100A/μs	t_{rr}	--	324	--	ns
Reverse Recovery Charge		Q_{rr}	--	4.8	--	μC

Notes:

1. Current limited by package.
2. Pulse width limited by the maximum junction temperature.
3. L = 50mH, V_{DD} = 50V, R_G = 25Ω, Starting T_J = 25ºC
4. Pulse test: PW ≤ 300μs, duty cycle ≤ 2%.
5. For DESIGN AID ONLY, not subject to production testing.
6. Switching time is essentially independent of operating temperature.


ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
TSM60NC390CP ROG	TO-252 (DPAK)	2,500pcs / 13” Reel


CHARACTERISTICS CURVES

(T_C = 25°C unless otherwise noted)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature




On-Resistance vs. Gate-Source Voltage




CHARACTERISTICS CURVES

(T_C = 25°C unless otherwise noted)


Capacitance vs. Drain-Source Voltage




BV_{DSS} vs. Junction Temperature




Maximum Safe Operating Area, Junction-to-Case



Source-Drain Diode Forward Current vs. Voltage




Normalized Thermal Transient Impedance, Junction-to-Case



PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

TO-252



MARKING DIAGRAM

60NC390 = Device marking
Y = Year Code
WW = Week Code (01~52)
L = Lot Code (1~9,A~Z)
F = Factory Code

NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. PACKAGE OUTLINE REFERENCE: JEDEC TO-252, VARIATION AA, ISSUE F.
4. MOLDED PLASTIC BODY DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSION, OR GATE BURRS.
5. DWG NO. REF: HQ2SD07-TO252AA-013 REV B.

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.