

- **Available in 2.5-V, 3-V, 3.3-V, 4.85-V, and 5-V Fixed-Output and Adjustable Versions**
- **Integrated Precision Supply-Voltage Supervisor Monitoring Regulator Output Voltage**
- **Active-Low Reset Signal with 200-ms Pulse Width**
- **Very Low Dropout Voltage . . . Maximum of 35 mV at I_O = 100 mA (TPS7350)**
- **Low Quiescent Current – Independent of Load . . . 340 μA Typ**
- **Extremely Low Sleep-State Current, 0.5 μA Max**
- **2% Tolerance Over Full Range of Load, Line, and Temperature for Fixed-Output Versions§**
- **Output Current Range of 0 mA to 500 mA**
- **TSSOP Package Option Offers Reduced Component Height For Critical Applications**

D OR P PACKAGE
(TOP VIEW)



PW PACKAGE
(TOP VIEW)



NC – No internal connection
† SENSE – Fixed voltage options only
(TPS7325, TPS7330, TPS7333, TPS7348, and TPS7350)
‡ FB – Adjustable version only (TPS7301)

description

The TPS73xx devices are members of a family of micropower low-dropout (LDO) voltage regulators. They are differentiated from the TPS71xx and TPS72xx LDOs by their integrated delayed microprocessor-reset function. If the precision delayed reset is not required, the TPS71xx and TPS72xx should be considered.¶

AVAILABLE OPTIONS

T_J	OUTPUT VOLTAGE (V)			NEGATIVE-GOING $\overline{\text{RESET}}$ THRESHOLD VOLTAGE (V)			PACKAGED DEVICES			CHIP FORM (Y)
	MIN	TYP	MAX	MIN	TYP	MAX	SMALL OUTLINE (D)	PLASTIC DIP (P)	TSSOP (PW)	
–40°C to 125°C	4.9	5	5.1	4.55	4.65	4.75	TPS7350QD	TPS7350QP	TPS7350QPW	TPS7350Y
	4.75	4.85	4.95	4.5	4.6	4.7	TPS7348QD	TPS7348QP	TPS7348QPW	TPS7348Y
	3.23	3.3	3.37	2.868	2.934	3	TPS7333QD	TPS7333QP	TPS7333QPW	TPS7333Y
	2.94	3	3.06	2.58	2.64	2.7	TPS7330QD	TPS7330QP	TPS7330QPW	TPS7330Y
	2.425	2.5	2.575	2.23	2.32	2.39	TPS7325QD	TPS7325QP	TPS7325QPW	TPS7325Y
	Adjustable 1.2 V to 9.75 V			1.101	1.123	1.145	TPS7301QD	TPS7301QP	TPS7301QPW	TPS7301Y

The D and PW packages are available taped and reeled. Add an R suffix to device type (e.g., TPS7350QDR). The TPS7301Q is programmable using an external resistor divider (see application information). The chip form is tested at 25°C.

§ The TPS7325 has a tolerance of ±3% over the full temperature range.
¶ The TPS71xx and the TPS72xx are 500-mA and 250-mA output regulators respectively, offering performance similar to that of the TPS73xx but without the delayed-reset function. The TPS72xx devices are further differentiated by availability in 8-pin thin-shrink small-outline packages (TSSOP) for applications requiring minimum package size.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 1999, Texas Instruments Incorporated

description (continued)

The $\overline{\text{RESET}}$ output of the TPS73xx initiates a reset in microcomputer and microprocessor systems in the event of an undervoltage condition. An internal comparator in the TPS73xx monitors the output voltage of the regulator to detect an undervoltage condition on the regulated output voltage.

If that occurs, the $\overline{\text{RESET}}$ output (open-drain NMOS) turns on, taking the $\overline{\text{RESET}}$ signal low. $\overline{\text{RESET}}$ stays low for the duration of the undervoltage condition. Once the undervoltage condition ceases, a 200-ms (typ) time-out begins. At the completion of the 200-ms delay, $\overline{\text{RESET}}$ goes high.

An order of magnitude reduction in dropout voltage and quiescent current over conventional LDO performance is achieved by replacing the typical pnp pass transistor with a PMOS device.

Because the PMOS device behaves as a low-value resistor, the dropout voltage is very low (maximum of 35 mV at an output current of 100 mA for the TPS7350) and is directly proportional to the output current (see Figure 1). Additionally, since the PMOS pass element is a voltage-driven device, the quiescent current is low and remains constant, independent of output loading (typically 340 μA over the full range of output current, 0 mA to 500 mA). These two key specifications yield a significant improvement in operating life for battery-powered systems.

The LDO family also features a sleep mode; applying a logic high signal to $\overline{\text{EN}}$ ($\overline{\text{enable}}$) shuts down the regulator, reducing the quiescent current to 0.5 μA maximum at T_J = 25°C.

The TPS73xx is offered in 2.5-V, 3-V, 3.3-V, 4.85-V, and 5-V fixed-voltage versions and in an adjustable version (programmable over the range of 1.2 V to 9.75 V). Output voltage tolerance is specified as a maximum of 2% over line, load, and temperature ranges (3% for the 2.5 V and the adjustable version). The TPS73xx family is available in PDIP (8 pin), SO (8 pin) and TSSOP (20 pin) packages. The TSSOP has a maximum height of 1.2 mm.





Figure 1. Dropout Voltage Versus Output Current



† TPS7325, TPS7330, TPS7333, TPS7348, TPS7350 (fixed-voltage options)


‡ Capacitor selection is nontrivial. See application information section for details.


Figure 2. Typical Application Configuration

TPS73xxY chip information

These chips, when properly assembled, display characteristics similar to those of the TPS73xxQ. Thermal compression or ultrasonic bonding may be used on the doped aluminum bonding pads. Chips may be mounted with conductive epoxy or a gold-silicon preform.

BONDING PAD ASSIGNMENTS





CHIP THICKNESS: 15 TYPICAL

BONDING PADS: 4 × 4 MINIMUM

$T_J$max = 150°C

TOLERANCES ARE ±10%.


ALL DIMENSIONS ARE IN MILS.

† SENSE – Fixed voltage options only (TPS7325, TPS7330, TPS7333, TPS7348, and TPS7350)

‡ FB – Adjustable version only (TPS7301)

NOTE A. For most applications, OUT and SENSE should be tied together as close as possible to the device; for other implementations, refer to SENSE-pin connection discussion in the applications information section of this data sheet.

functional block diagram



RESISTOR DIVIDER OPTIONS

DEVICE	R1	R2	UNIT
TPS7301	0	∞	Ω
TPS7325	260	233	kΩ
TPS7330	358	233	kΩ
TPS7333	420	233	kΩ
TPS7348	726	233	kΩ
TPS7350	756	233	kΩ


NOTE A. Resistors are nominal values only.

COMPONENT COUNT	
MOS transistors	464
Bilpolar transistors	41
Diodes	4
Capacitors	17
Resistors	76

§ For most applications, SENSE should be externally connected to OUT as close as possible to the device. For other implementations, refer to SENSE-pin connection discussion in applications information section.

¶ Switch positions are shown with $\overline{EN}$ low (active).

timing diagram



† V_{res} is the minimum input voltage for a valid $\overline{\text{RESET}}$. The symbol V_{res} is not currently listed within EIA or JEDEC standards for semiconductor symbology.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)‡

Input voltage range§, V_I, $\overline{\text{RESET}}$, SENSE, $\overline{\text{EN}}$	–0.3 V to 11 V
Output current, I_O	2 A
Continuous total power dissipation	See Dissipation Rating Tables 1 and 2
Operating virtual junction temperature range, T_J	–55°C to 150°C
Storage temperature range, T_{stg}	–65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	260°C

‡ Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

§ All voltage values are with respect to network terminal ground.

DISSIPATION RATING TABLE 1 – FREE-AIR TEMPERATURE (SEE FIGURE 3)

PACKAGE	$T_A \le 25°C$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25°C$	$T_A = 70°C$ POWER RATING	$T_A = 125°C$ POWER RATING
D	725 mW	5.8 mW/°C	464 mW	145 mW
P	1175 mW	9.4 mW/°C	752 mW	235 mW
PW†	700 mW	5.6 mW/°C	448 mW	140 mW

DISSIPATION RATING TABLE 2 – CASE TEMPERATURE (SEE FIGURE 4)

PACKAGE	$T_C \le 25°C$ POWER RATING	DERATING FACTOR ABOVE $T_C = 25°C$	$T_C = 70°C$ POWER RATING	$T_C = 125°C$ POWER RATING
D	2188 mW	9.4 mW/°C	1765 mW	1248 mW
P	2738 mW	21.9 mW/°C	1752 mW	548 mW
PW†	4025 mW	32.2 mW/°C	2576 mW	805 mW

† Refer to Thermal Information section for detailed power dissipation considerations when using the TSSOP package.

MAXIMUM CONTINUOUS DISSIPATION vs FREE-AIR TEMPERATURE




Figure 3

MAXIMUM CONTINUOUS DISSIPATION vs CASE TEMPERATURE




Figure 4

recommended operating conditions

		MIN	MAX	UNIT
Input voltage, V_I†	TPS7301Q	2.47	10	V
	TPS7325Q	3.1	10	
	TPS7330Q	3.5	10	V
	TPS7333Q	3.77	10	V
	TPS7348Q	5.2	10	
	TPS7350Q	5.33	10	
High-level input voltage at $\overline{EN}$, V_{IH}		2		V
Low-level input voltage at $\overline{EN}$, V_{IL}			0.5	V
Output current range, I_O		0	500	mA
Operating virtual junction temperature range, T_J		–40	125	°C

† Minimum input voltage defined in the recommended operating conditions is the maximum specified output voltage plus dropout voltage, V_{DO}, at the maximum specified load range. Since dropout voltage is a function of output current, the usable range can be extended for lighter loads. To calculate the minimum input voltage for the maximum load current used in a given application, use the following equation:

$$V_{I(min)} = V_{O(max)} + V_{DO(max\ load)}$$

Because the TPS7301 is programmable, $r_{DS(on)}$ should be used to calculate V_{DO} before applying the above equation. The equation for calculating V_{DO} from $r_{DS(on)}$ is given in Note 2 in the TPS7301 electrical characteristics table. The minimum value of 2.97 V is the absolute lower limit for the recommended input voltage range for the TPS7301.

electrical characteristics at I_O = 10 mA, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR‡ = 1 Ω), SENSE/FB shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS§	T_J	MIN	TYP	MAX	UNIT
Ground current (active mode)	$\overline{EN}$ ≤ 0.5 V, $V_I = V_O$ + 1 V, 0 mA ≤ I_O ≤ 500 mA	25°C		340	400	μA
		–40°C to 125°C			550	
Input current (standby mode)	EN = V_I, 2.7 V ≤ V_I ≤ 10 V	25°C		0.01	0.5	μA
		–40°C to 125°C			2	
Output current limit	V_O = 0 V, V_I = 10 V	25°C		1.2	2	A
		–40°C to 125°C			2	
Pass-element leakage current in standby mode	$\overline{EN}$ = V_I, 2.7 V ≤ V_I ≤ 10 V	25°C		0.01	0.5	μA
		–40°C to 125°C			1	
$\overline{RESET}$ leakage current	Normal operation, V at $\overline{RESET}$ = 10 V	25°C		0.02	0.5	μA
		–40°C to 125°C			0.5	
Output voltage temperature coefficient		–40°C to 125°C		61	75	ppm/°C
Thermal shutdown junction temperature				165		°C
$\overline{EN}$ logic high (standby mode)	2.5 V ≤ V_I ≤ 6 V	–40°C to 125°C	2			V
	6 V ≤ V_I ≤ 10 V		2.7			
EN logic low (active mode)	2.7 V ≤ V_I ≤ 10 V	25°C			0.5	V
		–40°C to 125°C			0.5	
$\overline{EN}$ hysteresis voltage		25°C		50		mV
$\overline{EN}$ input current	0 V ≤ V_I ≤ 10 V	25°C	–0.5	0.001	0.5	μA
		–40°C to 125°C	–0.5		0.5	
Minimum V_I for active pass element		25°C		2.05	2.5	V
		–40°C to 125°C			2.5	
Minimum V_I for valid $\overline{RESET}$	$I_{O(RESET)}$ = –300 μA	25°C		1	1.5	V
		–40°C to 125°C			1.9	

‡ CSR (compensation series resistance) refers to the total series resistance, including the equivalent series resistance (ESR) of the capacitor, any series resistance added externally, and PWB trace resistance to C_o.

§ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

TPS7301Q electrical characteristics at I_O = 10 mA, V_I = 3.5 V, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), FB shorted to OUT at device leads (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		T_J	MIN	TYP	MAX	UNIT
Reference voltage (measured at FB)			25°C		1.182		V
	2.5 V ≤ V_I ≤ 10 V, See Note 1	5 mA ≤ I_O ≤ 500 mA,	–40°C to 125°C	1.147		1.217	V
Reference voltage temperature coefficient			–40°C to 125°C		61	75	ppm/°C
Pass-element series resistance (See Note 2)	V_I = 2.4 V,	50 μA ≤ I_O ≤ 150 mA	25°C		0.7	1	Ω
			–40°C to 125°C			1	
	V_I = 2.4 V,	150 mA ≤ I_O ≤ 500 mA	25°C		0.83	1.3	
			–40°C to 125°C			1.3	
	V_I = 2.9 V,	50 μA ≤ I_O ≤ 500 mA	25°C		0.52	0.85	
			–40°C to 125°C			0.85	
	V_I = 3.9 V,	50 μA ≤ I_O ≤ 500 mA	25°C		0.32		
	V_I = 5.9 V,	50 μA ≤ I_O ≤ 500 mA	25°C		0.23		
Input regulation	V_I = 2.5 V to 10 V, See Note 1	50 μA ≤ I_O ≤ 500 mA,	25°C		3	18	mV
			–40°C to 125°C			25	
Output regulation	2.5 V ≤ V_I ≤ 10 V, See Note 1	I_O = 5 mA to 500 mA,	25°C		5	14	mV
			–40°C to 125°C			25	
	2.5 V ≤ V_I ≤ 10 V, See Note 1	I_O = 50 μA to 500 mA,	25°C		7	22	mV
			–40°C to 125°C			54	
Ripple rejection	f = 120 Hz	I_O = 50 μA	25°C	48	59		dB
			–40°C to 125°C	44			
		I_O = 500 mA, See Note 1	25°C	45	54		
			–40°C to 125°C	44			
Output noise-spectral density	f = 120 Hz		25°C		2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_o = 4.7 μF	25°C		95		μVrms
		C_o = 10 μF	25°C		89		
		C_o = 100 μF	25°C		74		
$\overline{RESET}$ trip-threshold voltage§	$V_{O(FB)}$ decreasing		–40°C to 125°C	1.101		1.145	V
$\overline{RESET}$ hysteresis voltage§	Measured at $V_{O(FB)}$		25°C		12		mV
$\overline{RESET}$ output low voltage§	V_I = 2.13 V,	$I_{O(RESET)}$ = 400 μA	25°C		0.1	0.4	V
			–40°C to 125°C			0.4	
FB input current			25°C	–10	0.1	10	nA
			–40°C to 125°C	–20		20	

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_o.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

§ Output voltage programmed to 2.5 V with closed-loop configuration (see application information).

NOTES: 1. When V_I < 2.9 V and I_O > 150 mA simultaneously, pass element $r_{DS(on)}$ increases (see Figure 33) to a point where the resulting dropout voltage prevents the regulator from maintaining the specified tolerance range.

2. To calculate dropout voltage, use equation: $V_{DO} = I_O \cdot r_{DS(on)}$
$r_{DS(on)}$ is a function of both output current and input voltage. This parametric table lists $r_{DS(on)}$ for V_I = 2.4 V, 2.9 V, 3.9 V, and 5.9 V, which corresponds to dropout conditions for programmed output voltages of 2.5 V, 3 V, 4 V, and 6 V respectively. For other programmed values, refer to Figure 33.

TPS7325Q electrical characteristics at I_O = 10 mA, V_I = 3.5 V, $\overline{EN}$ = 0 V, C_o = 10 μF (CSR† = 1 Ω), SENSE shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		T_J	MIN	TYP	MAX	UNIT
Output voltage			25°C	2.45	2.5	2.55	V
	3.5 V ≤ V_I ≤ 10 V,	5 mA ≤ I_O ≤ 500 mA	–40°C to 125°C	2.425		2.575	
Dropout voltage§	I_O = 10 mA,	V_I = 2.97 V	25°C		5		mV
			–40°C to 125°C			14	
	I_O = 100 mA,	V_I = 2.97 V	25°C		50	80	
			–40°C to 125°C			150	
	I_O = 500 mA,	V_I = 2.97 V	25°C		270	400	
			–40°C to 125°C			600	
Pass-element series resistance§	(2.97 V – V_O)/I_O, I_O = 500 mA	V_I = 2.97 V,	25°C		0.5	0.7	Ω
			–40°C to 125°C			1.4	
Input regulation	V_I = 3.5 V to 10 V,	50 μA ≤ I_O ≤ 500 mA	25°C		6	20	mV
			–40°C to 125°C			25	
Output regulation	I_O = 5 mA to 500 mA,	3.5 V ≤ V_I ≤ 10 V	25°C		20	32	mV
			–40°C to 125°C			50	
	I_O = 50 μA to 500 mA,	3.5 V ≤ V_I ≤ 10 V	25°C		28	60	mV
			–40°C to 125°C			100	
Ripple rejection	f = 120 Hz	I_O = 50 μA	25°C	50	53		dB
			–40°C to 125°C	49			
		I_O = 500 mA	25°C	49	53		
			–40°C to 125°C	32			
Output noise-spectral density	f = 120 Hz		25°C		2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_o = 4.7 μF	25°C		274		μVrms
		C_o = 10 μF	25°C		228		
		C_o = 100 μF	25°C		159		
$\overline{RESET}$ trip-threshold voltage	V_O decreasing		–40°C to 125°C	2.23	2.32	2.39	V
$\overline{RESET}$ output low voltage	V_I = 2.1 V,	$I_{O(RESET)}$ = –0.8 mA	25°C		0.14	0.4	V
			–40°C to 125°C			0.4	

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_o.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

§ Dropout test and pass-element series resistance test are not production tested. Test method requires SENSE terminal to be disconnected from output voltage.

TPS7330Q electrical characteristics at I_O = 10 mA, V_I = 4 V, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), SENSE shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		T_J	MIN	TYP	MAX	UNIT
Output voltage			25°C		3		V
	4 V ≤ V_I ≤ 10 V,	5 mA ≤ I_O ≤ 500 mA	–40°C to 125°C	2.94		3.06	
Dropout voltage	I_O = 10 mA,	V_I = 2.94 V	25°C		5.2	7	mV
			–40°C to 125°C			10	
	I_O = 100 mA,	V_I = 2.94 V	25°C		52	75	
			–40°C to 125°C			100	
	I_O = 500 mA,	V_I = 2.94 V	25°C		267	450	
			–40°C to 125°C			500	
Pass-element series resistance	(2.94 V – V_O)/I_O, I_O = 500 mA	V_I = 2.94 V,	25°C		0.5	0.7	Ω
			–40°C to 125°C			1	
Input regulation	V_I = 4 V to 10 V,	50 μA ≤ I_O ≤ 500 mA	25°C		6	23	mV
			–40°C to 125°C			29	
Output regulation	I_O = 5 mA to 500 mA,	4 V ≤ V_I ≤ 10 V	25°C		20	32	mV
			–40°C to 125°C			60	
	I_O = 50 μA to 500 mA,	4 V ≤ V_I ≤ 10 V	25°C		28	60	mV
			–40°C to 125°C			120	
Ripple rejection	f = 120 Hz	I_O = 50 μA	25°C	43	53		dB
			–40°C to 125°C	40			
		I_O = 500 mA	25°C	39	53		
			–40°C to 125°C	36			
Output noise-spectral density	f = 120 Hz		25°C		2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_o = 4.7 μF	25°C		274		μVrms
		C_o = 10 μF	25°C		228		
		C_o = 100 μF	25°C		159		
$\overline{RESET}$ trip-threshold voltage	V_O decreasing		–40°C to 125°C	2.58	2.64	2.7	V
$\overline{RESET}$ output low voltage	V_I = 2.6 V,	$I_{O(RESET)}$ = –0.8 mA	25°C		0.14	0.4	V
			–40°C to 125°C			0.4	

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_o.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

TPS7333Q electrical characteristics at I_O = 10 mA, V_I = 4.3 V, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), SENSE shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		T_J	MIN	TYP	MAX	UNIT
Output voltage			25°C		3.3		V
	4.3 V ≤ V_I ≤ 10 V,	5 mA ≤ I_O ≤ 500 mA	–40°C to 125°C	3.23		3.37	
Dropout voltage	I_O = 10 mA,	V_I = 3.23 V	25°C		4.5	7	mV
			–40°C to 125°C			8	
	I_O = 100 mA,	V_I = 3.23 V	25°C		44	60	
			–40°C to 125°C			80	
	I_O = 500 mA,	V_I = 3.23 V	25°C		235	300	
			–40°C to 125°C			400	
Pass-element series resistance	(3.23 V – V_O)/I_O, I_O = 500 mA	V_I = 3.23 V,	25°C		0.44	0.6	Ω
			–40°C to 125°C			0.8	
Input regulation	V_I = 4.3 V to 10 V,	50 μA ≤ I_O ≤ 500 mA	25°C		6	23	mV
			–40°C to 125°C			29	
Output regulation	I_O = 5 mA to 500 mA,	4.3 V ≤ V_I ≤ 10 V	25°C		21	38	mV
			–40°C to 125°C			75	
	I_O = 50 μA to 500 mA,	4.3 V ≤ V_I ≤ 10 V	25°C		31	60	mV
			–40°C to 125°C			120	
Ripple rejection	f = 120 Hz	I_O = 50 μA	25°C	43	51		dB
			–40°C to 125°C	40			
		I_O = 500 mA	25°C	39	49		
			–40°C to 125°C	36			
Output noise-spectral density	f = 120 Hz		25°C		2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_O = 4.7 μF	25°C		274		μVrms
		C_O = 10 μF	25°C		228		
		C_O = 100 μF	25°C		159		
$\overline{RESET}$ trip-threshold voltage	V_O decreasing		–40°C to 125°C	2.868			V
$\overline{RESET}$ hysteresis voltage			25°C		18		mV
$\overline{RESET}$ output low voltage	V_I = 2.8 V,	$I_{O(RESET)}$ = –1 mA	25°C		0.17	0.4	V
			–40°C to 125°C			0.4	

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_O.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

TPS7348Q electrical characteristics at I_O = 10 mA, V_I = 5.85 V, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), SENSE shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		T_J	MIN	TYP	MAX	UNIT
Output voltage			25°C		4.85		V
	5.85 V ≤ V_I ≤ 10 V,	5 mA ≤ I_O ≤ 500 mA	–40°C to 125°C	4.75		4.95	
Dropout voltage	I_O = 10 mA,	V_I = 4.75 V	25°C		2.9	6	mV
			–40°C to 125°C			8	
	I_O = 100 mA,	V_I = 4.75 V	25°C		28	37	
			–40°C to 125°C			54	
	I_O = 500 mA,	V_I = 4.75 V	25°C		150	180	
			–40°C to 125°C			250	
Pass-element series resistance	(4.75 V – V_O)/I_O, I_O = 500 mA	V_I = 4.75 V,	25°C		0.28	0.37	Ω
			–40°C to 125°C			0.52	
Input regulation	V_I = 5.85 V to 10 V,	50 μA ≤ I_O ≤ 500 mA	25°C		9	35	mV
			–40°C to 125°C			37	
Output regulation	I_O = 5 mA to 500 mA,	5.85 V ≤ V_I ≤ 10 V	25°C		28	42	mV
			–40°C to 125°C			80	
	I_O = 50 μA to 500 mA,	5.85 V ≤ V_I ≤ 10 V	25°C		42	65	mV
			–40°C to 125°C			130	
Ripple rejection	f = 120 Hz	I_O = 50 μA	25°C	42	53		dB
			–40°C to 125°C	39			
		I_O = 500 mA	25°C	39	50		
			–40°C to 125°C	35			
Output noise-spectral density	f = 120 Hz		25°C		2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_o = 4.7 μF	25°C		410		μVrms
		C_o = 10 μF	25°C		328		
		C_o = 100 μF	25°C		212		
$\overline{RESET}$ trip-threshold voltage	V_O decreasing		–40°C to 125°C	4.5		4.7	V
$\overline{RESET}$ hysteresis voltage			25°C		26		mV
$\overline{RESET}$ output low voltage	$I_{O(RESET)}$ = –1.2 mA, V_I = 4.12 V		25°C		0.2	0.4	V
			–40°C to 125°C			0.4	

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_O.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

TPS7350Q electrical characteristics at I_O = 10 mA, V_I = 6 V, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), SENSE shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		T_J	MIN	TYP	MAX	UNIT
Output voltage			25°C		5		V
	6 V ≤ V_I ≤ 10 V,	5 mA ≤ I_O ≤ 500 mA	–40°C to 125°C	4.9		5.1	
Dropout voltage	I_O = 10 mA,	V_I = 4.88 V	25°C		2.9	6	mV
			–40°C to 125°C			8	
	I_O = 100 mA,	V_I = 4.88 V	25°C		27	35	
			–40°C to 125°C			50	
	I_O = 500 mA,	V_I = 4.88 V	25°C		146	170	
			–40°C to 125°C			230	
Pass-element series resistance	(4.88 V – V_O)/I_O, I_O = 500 mA	V_I = 4.88 V,	25°C		0.27	0.35	Ω
			–40°C to 125°C			0.5	
Input regulation	V_I = 6 V to 10 V,	50 μA ≤ I_O ≤ 500 mA	25°C		4	25	mV
			–40°C to 125°C			45	
Output regulation	I_O = 5 mA to 500 mA,	6 V ≤ V_I ≤ 10 V	25°C		30	45	mV
			–40°C to 125°C			86	
	I_O = 50 μA to 500 mA,	6 V ≤ V_I ≤ 10 V	25°C		45	65	mV
			–40°C to 125°C			140	
Ripple rejection	f = 120 Hz	I_O = 50 μA	25°C	43	53		dB
			–40°C to 125°C	38			
		I_O = 500 mA	25°C	41	51		
			–40°C to 125°C	36			
Output noise-spectral density	f = 120 Hz		25°C		2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_o = 4.7 μF	25°C		430		μVrms
		C_o = 10 μF	25°C		345		
		C_o = 100 μF	25°C		220		
$\overline{RESET}$ trip-threshold voltage	V_O decreasing		–40°C to 125°C	4.55		4.75	V
$\overline{RESET}$ hysteresis voltage			25°C		28		mV
$\overline{RESET}$ output low voltage	$I_{O(RESET)}$ = –1.2 mA,	V_I = 4.25 V	25°C		0.15	0.4	V
			–40°C to 125°C			0.4	

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_O.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

switching characteristics

PARAMETER	TEST CONDITIONS	T_J	TPS7301Q, TPS7333Q TPS7348Q, TPS7350Q			UNIT
			MIN	TYP	MAX	
$\overline{\text{RESET}}$ time-out delay	See Figure 5	25°C	140	200	260	ms
		–40°C to 125°C	100		300	

electrical characteristics at I_O = 10 mA, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), T_J = 25°C, SENSE/FB shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		TPS7301Y, TPS7333Y TPS7348Y, TPS7350Y			UNIT
			MIN	TYP	MAX	
Ground current (active mode)	$\overline{EN} \le 0.5$ V, 0 mA ≤ I_O ≤ 500 mA	$V_I = V_O + 1$ V,		340		μA
Input current (standby mode)	$\overline{EN} = V_I$,	2.7 V ≤ V_I ≤ 10 V		0.01		μA
Output current limit	V_O = 0 V,	V_I = 10 V		1.2		A
Pass-element leakage current in standby mode	$\overline{EN} = V_I$,	2.7 V ≤ V_I ≤ 10 V		0.01		μA
$\overline{\text{RESET}}$ leakage current	Normal operation,	V at $\overline{\text{RESET}}$ = 10 V		0.02		μA
Thermal shutdown junction temperature				165		°C
$\overline{EN}$ logic low (active mode)	2.7 V ≤ V_I ≤ 10 V				0.5	V
$\overline{EN}$ hysteresis voltage				50		mV
$\overline{EN}$ input current	0 V ≤ V_I ≤ 10 V			0.001		μA
Minimum V_I for active pass element				2.05		V
Minimum V_I for valid $\overline{\text{RESET}}$	$I_{O(RESET)}$ = –300 μA			1		V

† CSR (compensation series resistance) refers to the total series resistance, including the equivalent series resistance (ESR) of the capacitor, any series resistance added externally, and PWB trace resistance to C_o.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

TPS7301Y electrical characteristics at I_O = 10 mA, V_I = 3.5 V, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), T_J = 25°C, FB shorted to OUT at device leads (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		MIN	TYP	MAX	UNIT
Reference voltage (measured at FB)				1.182		V
Pass-element series resistance (See Note 2)	V_I = 2.4 V,	50 μA ≤ I_O ≤ 150 mA		0.7		Ω
	V_I = 2.4 V,	150 mA ≤ I_O ≤ 500 mA		0.83		
	V_I = 2.9 V,	50 μA ≤ I_O ≤ 500 mA		0.52		
	V_I = 3.9 V,	50 μA ≤ I_O ≤ 500 mA		0.32		
	V_I = 5.9 V,	50 μA ≤ I_O ≤ 500 mA		0.23		
Input regulation	V_I = 2.5 V to 10 V, See Note 1	50 μA ≤ I_O ≤ 500 mA,		3		mV
Output regulation	2.5 V ≤ V_I ≤ 10 V, See Note 1	I_O = 5 mA to 500 mA,		5		mV
	2.5 V ≤ V_I ≤ 10 V, See Note 1	I_O = 50 μA to 500 mA,		7		mV
Ripple rejection	f = 120 Hz	I_O = 50 μA		59		dB
		I_O = 500 mA, See Note 1		54		
Output noise-spectral density	f = 120 Hz			2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_O = 4.7 μF		95		μVrms
		C_O = 10 μF		89		
		C_O = 100 μF		74		
$\overline{RESET}$ hysteresis voltage§	Measured at $V_{O(FB)}$			12		mV
$\overline{RESET}$ output low voltage§	V_I = 2.13 V,	$I_{O(RESET)}$ = 400 μA		0.1		V
FB input current				0.1		nA

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_O.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

§ Output voltage programmed to 2.5 V with closed-loop configuration (see application information).

NOTES: 1. When V_I < 2.9 V and I_O > 150 mA simultaneously, pass element $r_{DS(on)}$ increases (see Figure 33) to a point where the resulting dropout voltage prevents the regulator from maintaining the specified tolerance range.

2. To calculate dropout voltage, use equation: $V_{DO} = I_O \cdot r_{DS(on)}$
$r_{DS(on)}$ is a function of both output current and input voltage. The parametric table lists $r_{DS(on)}$ for V_I = 2.4 V, 2.9 V, 3.9 V, and 5.9 V, which corresponds to dropout conditions for programmed output voltages of 2.5 V, 3 V, 4 V, and 6 V respectively. For other programmed values, refer to Figure 33.

TPS7325Y electrical characteristics at I_O = 10 mA, V_I = 3.5 V, $\overline{EN}$ = 0 V, C_o = 10 μF (CSR† = 1 Ω), T_J = 25°C, SENSE shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		MIN	TYP	MAX	UNIT
Output voltage				2.5		V
Dropout voltage§	I_O = 10 mA,	V_I = 2.97 V		5		mV
	I_O = 100 mA,	V_I = 2.97 V		50		
	I_O = 500 mA,	V_I = 2.97 V		270		
Pass-element series resistance§	(2.97 V – V_O)/I_O, I_O = 500 mA	V_I = 2.97 V,		0.5		Ω
Input regulation	V_I = 3.5 V to 10 V,	50 μA ≤ I_O ≤ 500 mA		6		mV
Output regulation	I_O = 5 mA to 500 mA,	3.5 V ≤ V_I ≤ 10 V		20		mV
	I_O = 50 μA to 500 mA,	3.5 V ≤ V_I ≤ 10 V		28		mV
Ripple rejection	f = 120 Hz	I_O = 50 μA		53		dB
		I_O = 500 mA		53		
Output noise-spectral density	f = 120 Hz			2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_o = 4.7 μF		274		μVrms
		C_o = 10 μF		228		
		C_o = 100 μF		159		
$\overline{RESET}$ output low voltage	V_I = 2.1 V,	$I_{O(RESET)}$ = –0.8 mA		0.14		V

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_o.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

§ Dropout test and pass-element series resistance test are not production tested. Test method requires SENSE terminal to be disconnected from output voltage.

TPS7330Y electrical characteristics at I_O = 10 mA, V_I = 4 V, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), T_J = 25°C, SENSE shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		MIN	TYP	MAX	UNIT
Output voltage				3		V
Dropout voltage	I_O = 10 mA,	V_I = 2.94 V		5.2		mV
	I_O = 100 mA,	V_I = 2.94 V		52		
	I_O = 500 mA,	V_I = 2.94 V		267		
Pass-element series resistance	$(2.94\ V - V_O)/I_O$, I_O = 500 mA	V_I = 2.94 V,		0.5		Ω
Input regulation	V_I = 4 V to 10 V,	50 μA ≤ I_O ≤ 500 mA		6		mV
Output regulation	I_O = 5 mA to 500 mA,	4 V ≤ V_I ≤ 10 V		20		mV
	I_O = 50 μA to 500 mA,	4 V ≤ V_I ≤ 10 V		28		mV
Ripple rejection	f = 120 Hz	I_O = 50 μA		53		dB
		I_O = 500 mA		53		
Output noise-spectral density	f = 120 Hz			2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_o = 4.7 μF		274		μVrms
		C_o = 10 μF		228		
		C_o = 100 μF		159		
$\overline{RESET}$ output low voltage	V_I = 2.6 V,	$I_{O(RESET)}$ = −0.8 mA		0.14		V

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_O.
‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

TPS7333Y electrical characteristics at I_O = 10 mA, V_I = 4.3 V, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), T_J = 25°C, SENSE shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		MIN	TYP	MAX	UNIT
Output voltage				3.3		V
Dropout voltage	I_O = 10 mA,	V_I = 3.23 V		4.5		mV
	I_O = 100 mA,	V_I = 3.23 V		44		
	I_O = 500 mA,	V_I = 3.23 V		235		
Pass-element series resistance	$(3.23\ V - V_O)/I_O$, I_O = 500 mA	V_I = 3.23 V,		0.44		Ω
Input regulation	V_I = 4.3 V to 10 V,	50 μA ≤ I_O ≤ 500 mA		6		mV
Output regulation	I_O = 5 mA to 500 mA,	4.3 V ≤ V_I ≤ 10 V		21		mV
	I_O = 50 μA to 500 mA,	4.3 V ≤ V_I ≤ 10 V		31		mV
Ripple rejection	f = 120 Hz	I_O = 50 μA		51		dB
		I_O = 500 mA		49		
Output noise-spectral density	f = 120 Hz			2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_o = 4.7 μF		274		μVrms
		C_o = 10 μF		228		
		C_o = 100 μF		159		
$\overline{RESET}$ hysteresis voltage				18		mV
$\overline{RESET}$ output low voltage	V_I = 2.8 V,	$I_{O(RESET)}$ = −1 mA		0.17		V

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_O.
‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

TPS7348Y electrical characteristics at I_O = 10 mA, V_I = 5.85 V, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), T_J = 25°C, SENSE shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		MIN	TYP	MAX	UNIT
Output voltage				4.85		V
Dropout voltage	I_O = 10 mA,	V_I = 4.75 V		2.9		mV
	I_O = 100 mA,	V_I = 4.75 V		28		
	I_O = 500 mA,	V_I = 4.75 V		150		
Pass-element series resistance	(4.75 V – V_O)/I_O, I_O = 500 mA	V_I = 4.75 V,		0.28		Ω
Input regulation	V_I = 5.85 V to 10 V,	50 μA ≤ I_O ≤ 500 mA		9		mV
Output regulation	I_O = 5 mA to 500 mA,	5.85 V ≤ V_I ≤ 10 V		28		mV
	I_O = 50 μA to 500 mA,	5.85 V ≤ V_I ≤ 10 V		42		mV
Ripple rejection	f = 120 Hz	I_O = 50 μA		53		dB
		I_O = 500 mA		50		
Output noise-spectral density	f = 120 Hz			2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_o = 4.7 μF		410		μVrms
		C_o = 10 μF		328		
		C_o = 100 μF		212		
$\overline{RESET}$ hysteresis voltage				26		mV
$\overline{RESET}$ output low voltage	$I_{O(RESET)}$ = –1.2 mA,	V_I = 4.12 V		0.2		V

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_O.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

TPS7350Y electrical characteristics at I_O = 10 mA, V_I = 6 V, $\overline{EN}$ = 0 V, C_o = 4.7 μF (CSR† = 1 Ω), T_J = 25°C, SENSE shorted to OUT (unless otherwise noted)

PARAMETER	TEST CONDITIONS‡		MIN	TYP	MAX	UNIT
Output voltage				5		V
Dropout voltage	I_O = 10 mA,	V_I = 4.88 V		2.9	6	mV
	I_O = 100 mA,	V_I = 4.88 V		27	35	
	I_O = 500 mA,	V_I = 4.88 V		146	170	
Pass-element series resistance	(4.88 V – V_O)/I_O, I_O = 500 mA	V_I = 4.88 V,		0.27	0.35	Ω
Input regulation	V_I = 6 V to 10 V,	50 μA ≤ I_O ≤ 500 mA		4	25	mV
Output regulation	I_O = 5 mA to 500 mA,	6 V ≤ V_I ≤ 10 V		28	75	mV
	I_O = 50 μA to 500 mA,	6 V ≤ V_I ≤ 10 V		41		mV
Ripple rejection	f = 120 Hz	I_O = 50 μA		53		dB
		I_O = 500 mA		51		
Output noise-spectral density	f = 120 Hz			2		μV/√Hz
Output noise voltage	10 Hz ≤ f ≤ 100 kHz	C_o = 4.7 μF		430		μVrms
		C_o = 10 μF		345		
		C_o = 100 μF		220		
$\overline{RESET}$ hysteresis voltage				28		mV
$\overline{RESET}$ output low voltage	$I_{O(RESET)}$ = –1.2 mA,	V_I = 4.25 V		0.15	0.4	V

† CSR refers to the total series resistance, including the ESR of the capacitor, any series resistance added externally, and PWB trace resistance to C_O.

‡ Pulse-testing techniques are used to maintain virtual junction temperature as close as possible to ambient temperature; thermal effects must be taken into account separately.

PARAMETER MEASUREMENT INFORMATION





Figure 5. Test Circuit and Voltage Waveforms



† Ceramic capacitor

Figure 6. Test Circuit for Typical Regions of Stability (Refer to Figures 29 through 32)

TYPICAL CHARACTERISTICS

Table of Graphs

I_Q	Quiescent current		vs Output current	7
			vs Input voltage	8
I_Q	Quiescent current	TPS7348	vs Free-air temperature	9
I_Q	Quiescent current	TPS7325	vs Input voltage	10
			vs Free-air temperature	11
V_{DO}	Dropout voltage		vs Output current	12
ΔV_{DO}	Change in dropout voltage		vs Free-air temperature	13
V_{DO}	Dropout voltage	TPS7301	vs Output current	14
ΔV_O	Change in output voltage		vs Free-air temperature	15
V_O	Output voltage		vs Input voltage	16
V_O	Output voltage	TPS7325	vs Input voltage	17
	Line regulation			18
V_O	Output voltage	TPS7301	vs Output current	19
		TPS7325	vs Output current	20
		TPS7330	vs Output current	21
		TPS7333	vs Output current	22
		TPS7348	vs Output current	23
		TPS7350	vs Output current	24
	Output voltage response from enable ($\overline{EN}$)			25
	Load transient response	TPS7301 or TPS7333		26
		TPS7325		27
		TPS7348 or TPS7350		28
		TPS7301		29
		TPS7333		30
		TPS7348 or TPS7350		31
	Ripple rejection		vs Frequency	32
	Output spectral noise density		vs Frequency	33
	Compensation series resistance (CSR)	C_O = 4.7 µF	vs Output current	34
			vs Added ceramic capacitance	35
		C_O = 10 µF	vs Output current	36
			vs Added ceramic capacitance	37
$r_{DS(on)}$	Pass-element resistance		vs Input voltage	38
V_I	Minimum input voltage for valid $\overline{RESET}$		vs Free-air temperature	39
V_{IT-}	Negative-going reset threshold		vs Free-air temperature	40
$I_{OL(RESET)}$	$\overline{RESET}$ output current		vs Input voltage	41
t_d	Reset time delay		vs Free-air temperature	42
t_d	Distribution for reset delay			43

TYPICAL CHARACTERISTICS

QUIESCENT CURRENT vs OUTPUT CURRENT




Figure 7

QUIESCENT CURRENT vs INPUT VOLTAGE




Figure 8

TPS7348 QUIESCENT CURRENT vs FREE-AIR TEMPERATURE




Figure 9

TPS7325 QUIESCENT CURRENT vs INPUT VOLTAGE




Figure 10

TYPICAL CHARACTERISTICS

TPS7325
QUIESCENT CURRENT
vs
FREE-AIR TEMPERATURE




Figure 11

DROPOUT VOLTAGE
vs
OUTPUT CURRENT




Figure 12

CHANGE IN DROPOUT VOLTAGE
vs
FREE-AIR TEMPERATURE




Figure 13

TPS7301
DROPOUT VOLTAGE
vs
OUTPUT CURRENT




Figure 14

TYPICAL CHARACTERISTICS

CHANGE IN OUTPUT VOLTAGE vs FREE-AIR TEMPERATURE




Figure 15

OUTPUT VOLTAGE vs INPUT VOLTAGE




Figure 16

TPS7325 OUTPUT VOLTAGE vs INPUT VOLTAGE




Figure 17

LINE REGULATION




Figure 18

TYPICAL CHARACTERISTICS

TPS7301
OUTPUT VOLTAGE
vs
OUTPUT CURRENT




Figure 19

TPS7325
OUTPUT VOLTAGE
vs
OUTPUT CURRENT




Figure 20

TPS7330
OUTPUT VOLTAGE
vs
OUTPUT CURRENT




Figure 21

TPS7333
OUTPUT VOLTAGE
vs
OUTPUT CURRENT




Figure 22

TYPICAL CHARACTERISTICS

TPS7348
OUTPUT VOLTAGE
vs
OUTPUT CURRENT




Figure 23

TPS7350
OUTPUT VOLTAGE
vs
OUTPUT CURRENT




Figure 24

OUTPUT VOLTAGE RESPONSE FROM
ENABLE ($\overline{EN}$)




Figure 25

TYPICAL CHARACTERISTICS




Figure 26




Figure 27

TYPICAL CHARACTERISTICS




Figure 28




Figure 29

TYPICAL CHARACTERISTICS




Figure 30




Figure 31

TYPICAL CHARACTERISTICS

RIPPLE REJECTION
vs
FREQUENCY




Figure 32

OUTPUT SPECTRAL-NOISE DENSITY
vs
FREQUENCY




Figure 33

TYPICAL REGIONS OF STABILITY
COMPENSATION SERIES RESISTANCE (CSR)†
vs
OUTPUT CURRENT




Figure 34

TYPICAL REGIONS OF STABILITY
COMPENSATION SERIES RESISTANCE (CSR)†
vs
ADDED CERAMIC CAPACITANCE




Figure 35

TYPICAL CHARACTERISTICS

TYPICAL REGIONS OF STABILITY
COMPENSATION SERIES RESISTANCE (CSR)†
vs
OUTPUT CURRENT




Figure 36

TYPICAL REGIONS OF STABILITY
COMPENSATION SERIES RESISTANCE (CSR)†
vs
ADDED CERAMIC CAPACITANCE




Figure 37

PASS-ELEMENT RESISTANCE
vs
INPUT VOLTAGE




Figure 38

MINIMUM INPUT VOLTAGE FOR VALID $\overline{\text{RESET}}$
vs
FREE-AIR TEMPERATURE




Figure 39

TYPICAL CHARACTERISTICS

NEGATIVE-GOING RESET THRESHOLD vs FREE-AIR TEMPERATURE




Figure 40

$\overline{\text{RESET}}$ OUTPUT CURRENT vs INPUT VOLTAGE




Figure 41

RESET DELAY TIME vs FREE-AIR TEMPERATURE




Figure 42

DISTRIBUTION FOR RESET DELAY




Figure 43

THERMAL INFORMATION

In response to system-miniaturization trends, integrated circuits are being offered in low-profile and fine-pitch surface-mount packages. Implementation of many of today's high-performance devices in these packages requires special attention to power dissipation. Many system-dependent issues such as thermal coupling, airflow, added heat sinks and convection surfaces, and the presence of other heat-generating components affect the power-dissipation limits of a given component.

Three basic approaches for enhancing thermal performance are illustrated in this discussion:

- Improving the power-dissipation capability of the PWB design
- Improving the thermal coupling of the component to the PWB
- Introducing airflow in the system

Figure 44 is an example of a thermally enhanced PWB layout for the 20-lead TSSOP package. This layout involves adding copper on the PWB to conduct heat away from the device. The $R_{\theta JA}$ (thermal resistance, junction-to-ambient) for this component/board system is illustrated in Figure 45. The family of curves illustrates the effect of increasing the size of the copper-heat-sink surface area. The PWB is a standard FR4 board ($L \times W \times H$ = 3.2 inch $\times$ 3.2 inch $\times$ 0.062 inch); the board traces and heat sink area are 1-oz (per square foot) copper.

Figure 46 shows the thermal resistance for the same system with the addition of a thermally-conductive compound between the body of the TSSOP package and the PWB copper routed directly beneath the device. The thermal conductivity for the compound used in this analysis is 0.815 W/m $\times$ °C.

Using these figures to determine the system $R_{\theta JA}$ allows the maximum power-dissipation limit to be calculated with the equation:

$$P_{D(max)} = \frac{T_{J(max)} - T_A}{R_{\theta JA(system)}}$$

Where

$T_{J(max)}$ is the maximum allowable junction temperature; 150°C absolute maximum and 125°C maximum recommended operating temperature for specified operation.

This limit should then be applied to the internal power dissipated by the TPS73xx regulator. The equation for calculating total internal power dissipation of the TPS73xx is:

$$P_{D(total)} = \left(V_I - V_O\right) \times I_O + V_I \times I_Q$$

Because the quiescent current of the TPS73xx family is very low, the second term is negligible, further simplifying the equation to:

$$P_{D(total)} = \left(V_I - V_O\right) \times I_O$$

For a 20-lead TSSOP/FR4 board system with thermally conductive compound between the board and the device body, where T_A = 55°C, airflow = 100 ft/min, and copper heat sink area = 1 cm^2, the maximum power-dissipation limit can be calculated. As indicated in Figure 46, the system $R_{\theta JA}$ is 94°C/W; therefore, the maximum power-dissipation limit is:

$$P_{D(max)} = \frac{T_{J(max)} - T_A}{R_{\theta JA(system)}} = \frac{125^\circ C - 55^\circ C}{94^\circ C/W} = 745 \text{ mW}$$

If the system implements a TPS7348 regulator where V_I = 6 V and I_O = 150 mA, the internal power dissipation is:

$$P_{D(total)} = \left(V_I - V_O\right) \times I_O = (6 - 4.85) \times 0.150 = 173 \text{ mW}$$

THERMAL INFORMATION

Comparing $P_{D(total)}$ with $P_{D(max)}$ reveals that the power dissipation in this example does not exceed the maximum limit. When it does, one of two corrective actions can be taken. The power-dissipation limit can be raised by increasing either the airflow or the heat-sink area. Alternatively, the internal power dissipation of the regulator can be lowered by reducing either the input voltage or the load current. In either case, the above calculations should be repeated with the new system parameters.




Figure 44. Thermally Enhanced PWB Layout (not to scale) for the 20-Pin TSSOP




Figure 45




Figure 46

APPLICATION INFORMATION

The TPS73xx series of low-dropout (LDO) regulators overcome many of the shortcomings of earlier generation LDOs, while adding features such as a power-saving shutdown mode and a supply-voltage supervisor. The TPS73xx family includes five fixed-output voltage regulators: the TPS7325 (2.5 V), TPS7330 (3 V), TPS7333 (3.3 V), the TPS7348 (4.85 V), and the TPS7350 (5 V). The family also offers an adjustable device, the TPS7301 (adjustable from 1.2 V to 9.75 V).

device operation

The TPS73xx, unlike many other LDOs, features very low quiescent currents that remain virtually constant even with varying loads. Conventional LDO regulators use a pnp-pass element, the base current of which is directly proportional to the load current through the regulator ($I_B = I_C/\beta$). Close examination of the data sheets reveals that such devices are typically specified under near no-load conditions; actual operating currents are much higher as evidenced by typical quiescent current versus load current curves (see Figure 7). The TPS73xx uses a PMOS transistor to pass current; because the gate of the PMOS element is voltage driven, operating currents are low and invariable over the full load range. The TPS73xx specifications reflect actual performance under load.

Another pitfall associated with the pnp-pass element is its tendency to saturate when the device goes into dropout. The resulting drop in β forces an increase in I_B to maintain the load. During power-up, this translates to large start-up currents. Systems with limited supply current may fail to start up. In battery-powered systems, it means rapid battery discharge when the voltage decays below the minimum required for regulation. The TPS73xx quiescent current remains low even when the regulator drops out, thus eliminating both problems.

Included in the TPS73xx family is a 4.85-V regulator, the TPS7348. Designed specifically for 5-V cellular systems, its 4.85-V output, regulated to within $\pm$ 2%, allows for operation within the low-end limit of 5-V systems specified to $\pm$ 5% tolerance; therefore, maximum regulated operating lifetime is obtained from a battery pack before the device drops out, adding crucial talk minutes between charges.

The TPS73xx family also features a shutdown mode that places the output in the high-impedance state (essentially equal to the feedback-divider resistance) and reduces quiescent current to under 0.5 μA. When the shutdown feature is not used, $\overline{EN}$ should be tied to ground. Response to an enable transition is quick; regulated output voltage is reestablished in typically 120 μs.

minimum load requirements

The TPS73xx family is stable even at zero load; no minimum load is required for operation.

SENSE connection

The SENSE terminal of fixed-output devices must be connected to the regulator output for proper functioning of the regulator. Normally, this connection should be as short as possible; however, the connection can be made near a critical circuit (remote sense) to improve performance at that point. Internally, SENSE connects to a high-impedance wide-bandwidth amplifier through a resistor-divider network, and noise pickup feeds through to the regulator output. It is essential to route the SENSE connection in such a way as to minimize/avoid noise pickup. Adding an RC network between SENSE and OUT to filter noise is not recommended because it can cause the regulator to oscillate.

external capacitor requirements

An input capacitor is not required; however, a ceramic bypass capacitor (0.047 pF to 0.1 μF) improves load transient response and noise rejection when the TPS73xx is located more than a few inches from the power supply. A higher-capacitance electrolytic capacitor may be necessary if large (hundreds of milliamps) load transients with fast rise times are anticipated.

APPLICATION INFORMATION

external capacitor requirements (continued)

As with most LDO regulators, the TPS73xx family requires an output capacitor for stability. A low-ESR 10-μF solid-tantalum capacitor connected from the regulator output to ground is sufficient to ensure stability over the full load range (see Figure 42). Adding high-frequency ceramic or film capacitors (such as power-supply bypass capacitors for digital or analog ICs) can cause the regulator to become unstable unless the ESR of the tantalum capacitor is less than 1.2 Ω over temperature. Capacitors with published ESR specifications such as the AVX TPSD106M035R0300 and the Sprague 593D106X0035D2W work well because the maximum ESR at 25°C is 300 mΩ (typically, the ESR in solid-tantalum capacitors increases by a factor of 2 or less when the temperature drops from 25°C to –40°C). Where component height and/or mounting area is a problem, physically smaller, 10-μF devices can be screened for ESR. Figures 29 through 32 show the stable regions of operation using different values of output capacitance with various values of ceramic load capacitance.

In applications with little or no high-frequency bypass capacitance (< 0.2 μF), the output capacitance can be reduced to 4.7 μF, provided ESR is maintained between 0.7 and 2.5 Ω. Because capacitor minimum ESR is seldom if ever specified, it may be necessary to add a 0.5-Ω to 1-Ω resistor in series with the capacitor and limit ESR to 1.5 Ω maximum. As shown in the CSR graphs (Figures 29 through 32), minimum ESR is not a problem when using 10-μF or larger output capacitors.

Below is a partial listing of surface-mount capacitors usable with the TPS73xx family. This information, along with the CSR graphs, is included to assist in selection of suitable capacitance for the user's application. When necessary to achieve low height requirements along with high output current and/or high ceramic load capacitance, several higher ESR capacitors can be used in parallel to meet the guidelines above.

All load and temperature conditions with up to 1 μF of added ceramic load capacitance:

PART NO.	MFR.	VALUE	MAX ESR†	SIZE (H × L × W)†
T421C226M010AS	Kemet	22 μF, 10 V	0.5	2.8 × 6 × 3.2
593D156X0025D2W	Sprague	15 μF, 25 V	0.3	2.8 × 7.3 × 4.3
593D106X0035D2W	Sprague	10 μF, 35 V	0.3	2.8 × 7.3 × 4.3
TPSD106M035R0300	AVX	10 μF, 35 V	0.3	2.8 × 7.3 × 4.3

Load < 200 mA, ceramic load capacitance < 0.2 μF, full temperature range:

PART NO.	MFR.	VALUE	MAX ESR†	SIZE (H × L × W)†
592D156X0020R2T	Sprague	15 μF, 20 V	1.1	1.2 × 7.2 × 6
595D156X0025C2T	Sprague	15 μF, 25 V	1	2.5 × 7.1 × 3.2
595D106X0025C2T	Sprague	10 μF, 25 V	1.2	2.5 × 7.1 × 3.2
293D226X0016D2W	Sprague	22 μF, 16 V	1.1	2.8 × 7.3 × 4.3


Load < 100 mA, ceramic load capacitance < 0.2 μF, full temperature range:

PART NO.	MFR.	VALUE	MAX ESR†	SIZE (H × L × W)†
195D106X06R3V2T	Sprague	10 μF, 6.3 V	1.5	1.3 × 3.5 × 2.7
195D106X0016X2T	Sprague	10 μF, 16 V	1.5	1.3 × 7 × 2.7
595D156X0016B2T	Sprague	15 μF, 16 V	1.8	1.6 × 3.8 × 2.6
695D226X0015F2T	Sprague	22 μF, 15 V	1.4	1.8 × 6.5 × 3.4
695D156X0020F2T	Sprague	15 μF, 20 V	1.5	1.8 × 6.5 × 3.4
695D106X0035G2T	Sprague	10 μF, 35 V	1.3	2.5 × 7.6 × 2.5

† Size is in mm. ESR is maximum resistance at 100 kHz and T_A = 25°C. Listings are sorted by height.

APPLICATION INFORMATION

external capacitor requirements (continued)



† TPS7333, TPS7348, TPS7350 (fixed-voltage options)

Figure 47. Typical Application Circuit

programming the TPS7301 adjustable LDO regulator

Programming the adjustable regulators is accomplished using an external resistor divider as shown in Figure 43. The equation governing the output voltage is:

$$V_O = V_{ref} \times \left(1 + \frac{R1}{R2}\right)$$


Where

V_{ref} = reference voltage, 1.182 V typ

APPLICATION INFORMATION

Resistors R1 and R2 should be chosen for approximately 7-μA divider current. A recommended value for R2 is 169 kΩ with R1 adjusted for the desired output voltage. Smaller resistors can be used, but offer no inherent advantage and consume more power. Larger values of R1 and R2 should be avoided as leakage currents at FB will introduce an error. Solving for R1 yields a more useful equation for choosing the appropriate resistance:

$$R1 = \left(\frac{V_O}{V_{ref}} - 1\right) \times R2$$



OUTPUT VOLTAGE PROGRAMMING GUIDE

OUTPUT VOLTAGE	R1	R2	UNIT
2.5 V	191	169	kΩ
3.3 V	309	169	kΩ
3.6 V	348	169	kΩ
4 V	402	169	kΩ
5 V	549	169	kΩ
6.4 V	750	169	kΩ

Figure 48. TPS7301 Adjustable LDO Regulator Programming

undervoltage supervisor function

The $\overline{\text{RESET}}$ output of the TPS73xx initiates a reset in microcomputer and microprocessor systems in the event of an undervoltage condition. An internal comparator in the TPS73xx monitors the output voltage of the regulator to detect the undervoltage condition. When that occurs, the $\overline{\text{RESET}}$ output transistor turns on taking the $\overline{\text{RESET}}$ signal low.

On power up, the output voltage tracks the input voltage. The $\overline{\text{RESET}}$ output becomes active (low) as V_I approaches the minimum required for a valid $\overline{\text{RESET}}$ signal (specified at 1.5 V for 25°C and 1.9 V over full recommended operating temperature range). When the output voltage reaches the appropriate positive-going input threshold (V_{IT+}), a 200-ms (typical) timeout period begins during which the $\overline{\text{RESET}}$ output remains low. Once the timeout has expired, the $\overline{\text{RESET}}$ output becomes inactive. Since the $\overline{\text{RESET}}$ output is an open-drain NMOS, a pullup resistor should be used to ensure that a logic-high signal is indicated.

The supply-voltage-supervisor function is also activated during power-down. As the input voltage decays and after the dropout voltage is reached, the output voltage tracks linearly with the decaying input voltage. When the output voltage drops below the specified negative-going input threshold (V_{IT-} — see electrical characteristics tables), the $\overline{\text{RESET}}$ output becomes active (low). It is important to note that if the input voltage decays below the minimum required for a valid $\overline{\text{RESET}}$, the $\overline{\text{RESET}}$ is undefined.

Since the circuit is monitoring the regulator output voltage, the $\overline{\text{RESET}}$ output can also be triggered by disabling the regulator or by any fault condition that causes the output to drop below V_{IT-}. Examples of fault conditions include a short circuit on the output and a low input voltage. Once the output voltage is reestablished, either by reenabling the regulator or removing the fault condition, then the internal timer is initiated, which holds the $\overline{\text{RESET}}$ signal active during the 200-ms (typical) timeout period.

APPLICATION INFORMATION

undervoltage supervisor function (continued)

Transient loads or line pulses can also cause a reset to occur if proper care is not taken in selecting the input and output capacitors. Load transients that are faster than 5 μs can cause a reset if high-ESR output capacitors (greater than approximately 7 Ω) are used. A 1-μs transient causes a reset when using an output capacitor with greater than 3.5 Ω of ESR. Note that the output-voltage spike during the transient can drop well below the reset threshold and still not trip if the transient duration is short. A 1-μs transient must drop at least 500 mV below the threshold before tripping the reset circuit. A 2-μs transient trips $\overline{\text{RESET}}$ at just 400 mV below the threshold. Lower-ESR output capacitors help by reducing the drop in output voltage during a transient and should be used when fast transients are expected.

NOTE:

$V_{IT+} = V_{IT-}$ +Hysteresis

output noise

The TPS73xx has very low output noise, with a spectral noise density < 2 $\mu V/\sqrt{Hz}$. This is important when noise-susceptible systems, such as audio amplifiers, are powered by the regulator.

regulator protection

The TPS73xx PMOS-pass transistor has a built-in back diode that safely conducts reverse currents when the input voltage drops below the output voltage (e.g., during power down). Current is conducted from the output to the input and is not internally limited. If extended reverse voltage is anticipated, external limiting might be appropriate.

The TPS73xx also features internal current limiting and thermal protection. During normal operation, the TPS73xx limits output current to approximately 1 A. When current limiting engages, the output voltage scales back linearly until the overcurrent condition ends. While current limiting is designed to prevent gross device failure, care should be taken not to exceed the power dissipation ratings of the package. If the temperature of the device exceeds 165°C, thermal-protection circuitry shuts it down. Once the device has cooled, regulator operation resumes.

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
TPS7301QD	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7301Q
TPS7301QD.A	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7301Q
TPS7301QDG4	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7301Q
TPS7301QDR	NRND	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7301Q
TPS7301QDR.A	NRND	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7301Q
TPS7301QP	Active	Production	PDIP (P) | 8	50 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 125	TPS7301QP
TPS7301QP.A	Active	Production	PDIP (P) | 8	50 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 125	TPS7301QP
TPS7301QPW	Active	Production	TSSOP (PW) | 20	70 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	PT7301
TPS7301QPW.A	Active	Production	TSSOP (PW) | 20	70 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	PT7301
TPS7325QD	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	7325Q
TPS7325QD.A	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	7325Q
TPS7325QP	Active	Production	PDIP (P) | 8	50 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 85	TPS7325QP
TPS7325QP.A	Active	Production	PDIP (P) | 8	50 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 85	TPS7325QP
TPS7325QPWR	Active	Production	TSSOP (PW) | 20	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	PT7325
TPS7325QPWR.A	Active	Production	TSSOP (PW) | 20	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 85	PT7325
TPS7330QD	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7330Q
TPS7330QD.A	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7330Q
TPS7330QDR	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7330Q
TPS7330QDR.A	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7330Q
TPS7330QP	Active	Production	PDIP (P) | 8	50 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 125	TPS7330QP
TPS7330QP.A	Active	Production	PDIP (P) | 8	50 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 125	TPS7330QP
TPS7333QD	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7333Q
TPS7333QD.A	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7333Q
TPS7333QDG4	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7333Q
TPS7333QDR	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7333Q
TPS7333QDR.A	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7333Q
TPS7333QDRG4	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7333Q
TPS7333QP	Active	Production	PDIP (P) | 8	50 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 125	TPS7333QP
TPS7333QP.A	Active	Production	PDIP (P) | 8	50 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 125	TPS7333QP

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
TPS7333QPW	Active	Production	TSSOP (PW) | 20	70 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	PT7333
TPS7333QPW.A	Active	Production	TSSOP (PW) | 20	70 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	PT7333
TPS7333QPWR	Active	Production	TSSOP (PW) | 20	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	PT7333
TPS7333QPWR.A	Active	Production	TSSOP (PW) | 20	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	PT7333
TPS7348QDR	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7348Q
TPS7348QDR.A	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7348Q
TPS7350QD	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7350Q
TPS7350QD.A	Active	Production	SOIC (D) | 8	75 | TUBE	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7350Q
TPS7350QDR	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7350Q
TPS7350QDR.A	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	7350Q
TPS7350QP	Active	Production	PDIP (P) | 8	50 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 125	TPS7350QP
TPS7350QP.A	Active	Production	PDIP (P) | 8	50 | TUBE	Yes	NIPDAU	N/A for Pkg Type	-40 to 125	TPS7350QP
TPS7350QPWR	Active	Production	TSSOP (PW) | 20	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	PT7350
TPS7350QPWR.A	Active	Production	TSSOP (PW) | 20	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-40 to 125	PT7350

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.


Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

REEL DIMENSIONS




TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers


QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPS7301QDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TPS7325QPWR	TSSOP	PW	20	2000	330.0	16.4	6.95	7.0	1.4	8.0	16.0	Q1
TPS7330QDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TPS7333QDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TPS7333QPWR	TSSOP	PW	20	2000	330.0	16.4	6.95	7.0	1.4	8.0	16.0	Q1
TPS7348QDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TPS7350QDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TPS7350QPWR	TSSOP	PW	20	2000	330.0	16.4	6.95	7.0	1.4	8.0	16.0	Q1


TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TPS7301QDR	SOIC	D	8	2500	350.0	350.0	43.0
TPS7325QPWR	TSSOP	PW	20	2000	353.0	353.0	32.0
TPS7330QDR	SOIC	D	8	2500	350.0	350.0	43.0
TPS7333QDR	SOIC	D	8	2500	350.0	350.0	43.0
TPS7333QPWR	TSSOP	PW	20	2000	353.0	353.0	32.0
TPS7348QDR	SOIC	D	8	2500	350.0	350.0	43.0
TPS7350QDR	SOIC	D	8	2500	350.0	350.0	43.0
TPS7350QPWR	TSSOP	PW	20	2000	353.0	353.0	32.0

TUBE



*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	L (mm)	W (mm)	T (µm)	B (mm)
TPS7301QD	D	SOIC	8	75	505.46	6.76	3810	4
TPS7301QD.A	D	SOIC	8	75	505.46	6.76	3810	4
TPS7301QDG4	D	SOIC	8	75	505.46	6.76	3810	4
TPS7301QP	P	PDIP	8	50	506	13.97	11230	4.32
TPS7301QP.A	P	PDIP	8	50	506	13.97	11230	4.32
TPS7301QPW	PW	TSSOP	20	70	530	10.2	3600	3.5
TPS7301QPW.A	PW	TSSOP	20	70	530	10.2	3600	3.5
TPS7325QD	D	SOIC	8	75	505.46	6.76	3810	4
TPS7325QD.A	D	SOIC	8	75	505.46	6.76	3810	4
TPS7325QP	P	PDIP	8	50	506	13.97	11230	4.32
TPS7325QP.A	P	PDIP	8	50	506	13.97	11230	4.32
TPS7330QD	D	SOIC	8	75	505.46	6.76	3810	4
TPS7330QD.A	D	SOIC	8	75	505.46	6.76	3810	4
TPS7330QP	P	PDIP	8	50	506	13.97	11230	4.32
TPS7330QP.A	P	PDIP	8	50	506	13.97	11230	4.32
TPS7333QD	D	SOIC	8	75	505.46	6.76	3810	4
TPS7333QD.A	D	SOIC	8	75	505.46	6.76	3810	4
TPS7333QDG4	D	SOIC	8	75	505.46	6.76	3810	4
TPS7333QP	P	PDIP	8	50	506	13.97	11230	4.32
TPS7333QP.A	P	PDIP	8	50	506	13.97	11230	4.32
TPS7333QPW	PW	TSSOP	20	70	530	10.2	3600	3.5
TPS7333QPW.A	PW	TSSOP	20	70	530	10.2	3600	3.5
TPS7350QD	D	SOIC	8	75	505.46	6.76	3810	4
TPS7350QD.A	D	SOIC	8	75	505.46	6.76	3810	4
TPS7350QP	P	PDIP	8	50	506	13.97	11230	4.32
TPS7350QP.A	P	PDIP	8	50	506	13.97	11230	4.32

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI’s products are provided subject to TI’s Terms of Sale, TI’s General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI’s provision of these resources does not expand or otherwise alter TI’s applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.